

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	FALCON LEASE PTE 60 PAYA LEBAR ROA		R SQUARE, SINGAPORE, 4	Owner No.: <u>FLNU 501732-5</u>	
Manufacturer	JINGJIANG ASIAN-P.	ACIFIC LOGISTICS EQU	IIPMENT CO., LTD	Serial No.: <u>2202445</u>	
& address		VENUE, JINGJIANG, CH	<u>IINA, 214500</u>		
Manufacturer's Model Nº.: A023E	<u>-020-0003</u>				
APPLICABLE RULES, REGULA	TIONS AND STANDAR	DS			
ABS Design Type №: <u>AB/119/22</u>		_	US DOT Identification Cod	e: <u>IA-8101</u>	
ABS Approval Ref. Nº: <u>T2232130</u>			US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>		
CSC Approval Reference: USA/AB-119/22			IMDG Approval Reference: USA/IMO/AB/119/22		
Customs Approval Reference: USA/119-AB/22			Sec. 6.7 ADR/RID Approval Number: NL/AB-119/22		
International Union of Railways (UIC): IRS 50592		Sec. 6.8 ADR/RID Approval Number: NL/AB-119/22			
Other(s): <u>TC, ISO 668, 1161, 634</u>			US DoT SP: <u>N/A</u> and/or TC	CEquiv.Cert.: <u>N/A</u>	
	S				
ISO Size/Type Code: 22K2			bi 0400 mm	Ligiskt 2504 mm	
Overall Length: <u>6058</u> mm Maximum Operating Gross Mass:	26000 kg		h: <u>2438</u> mm	Height <u>2591</u> mm Max. Permissible Payload: <u>32390</u> kg	
Allowable Stacking Load for 1.8 g		Tar	e: <u>3610</u> kg Transverse Racking Test F		
TANK CHARACTERISTICS	. <u>210000</u> Ng		Transverse Racking react	10000 newtons	
Design Code: ASME BPVC.VIII.1	& EN 14025		Liquid Capacity at 20°C: 24	1990 liters (total)	
Overall Tank Length: 6009 mm	<u>1 G LIN 14020</u>		Outside Tank Diameter: 23		
Head Matl Spec.: SANS 50028-7:	1.4402	Head Thickness: 4.6 mm		Head Corrosion Allowance: 0.3 mm	
Shell Matl Spec.: SANS 50028-7:		Shell Thickness: <u>4.6</u> mm		Shell Corrosion Allowance: <u>0.42</u> mm	
Equiv. Reference Steel Thickness					
MAWP: <u>4</u> bar			MAWP of Heating System:	<u>4</u> bar	
External Design Pressure: 0.41 bar			Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C		
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm		- 11	Insulation: Type: Rockwool & Thickness: 50 mm		
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: <u>GRP</u> & Thickness: <u>1.8/2.0</u> mm		
Discharge: Bottom			Bottom Discharge No. of C	losures in Series: <u>Enter</u>	
PRESSURE RELIEF DEVICES					
	1 st ; Quantity: <u>1</u>		2 nd ; Quantity:	3 rd ; Quantity:	
Manufacturer	Fort Vale				
Catalog Number Set Pressure	010/144000 4.4 bar			bar	
Rupture	<u>4.4</u> bar <u>N/A</u> bar		bar bar	bar	
Capacity (each)	<u>3.922</u> m ³ /s		<u></u> m ³ /s	m³/s	
Total Capacity: <u>3.922</u> m ³ /s				T	
SERVICE EQUIPMENT					
Fort Vale 3" Bottom Discharge, 1	.5" Air line, 3" Top Disch	arge Provision			
TESTING INFORMATION					
Prototype Test Certificate: SQ516	0305-A. dated: 12-Mar-2	2022	Rail Impact Test Certificate	P/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>	
TC Impact Approved: Yes				······································	
PRESSURE TEST					
Test Pressure of Tank: 6 bar, date	ed: 05-Apr-2022		Test Pressure of Heating S	System: <u>6</u> bar, dated: <u>04-Apr-2022</u>	
Leak Proof Test of Container: <u>1</u> ba				<u> </u>	
Approved Commodities: Compatil	· · · ·	er T11 / L4BN			
Portable Tank Instruction: T11			ADR/RID Tank Code: L4B	<u>N</u>	
Marking: 05/04/2022 P B			CSC Plate Stamping Date: <u>04/2022</u> or ACEP №.: <u>N/A</u>		
			Next Inspection Date: <u>10/2</u>	024	
Stamping tank-pla		veen commodities and so		lief devices/vessel/gaskets are the responsibility of the	
owner. Shipping name/special pro	ovisions markings are the	e responsibility of the own	er.		
Issued on: 15-Apr-2022 at Jingjia	ng, Jiangsu, China by <u>Sh</u>	en, Songxian (Empl. No.		Field Office: ABS Shangha	
Request Reviewed and NO Con	flict of Interest Identified.			s \	
				2	
NOTE: This Certificate evidences com	pliance with one or more of t	he Rules, guides, standards,	or other criter and metican Bur	au of Shipping and is issued solely for the use of the Bureau, it	
committees, its clients or other guides, standards, or other crite	authorized entities. This Cer eria of American Bureau of Sh	tificate is a representation or hipping. The validity, applicabi	ily that the Contained of the Certi	au of Shipping and is issued solely for the use of the Bureau, it I herein has been found to comply with one or more of the Rules ficate is governed by the Rules and standards of American Burea	
of Shipping who shall remain th builder, owner, manufacturer, s	e sole judge thereof. Nothing	contained in this Certificate	or in any Report issued in coptem	ation of this Certificate shall be deemed to relieve any designe	