

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Certificate Nº: SQ5236463-61

Owner No.: FLNU 501736-7

Owner FALCON LEASE PTE LTD.

& address 60 PAYA LEBAR ROAD, #12-05, PAYA LEBAR SQUARE, SINGAPORE, 409051

Manufacturer <u>JINGJIANG ASIAN-PACIFIC LOGISTICS EQUIPMENT CO., LTD</u> & address <u>NO. 199 XINGANG AVENUE, JINGJIANG, CHINA, 214500</u> Serial No.: <u>2202449</u>

Manufacturer's Model Nº.: A023E-025-0003

APPLICABLE RULES, REGULATIONS AND STANDARDS

ABS Design Type №: <u>AB/119/22</u> US DOT Identification Code: <u>IA-8101</u>

ABS Approval Ref. №: <u>T2232130</u> US DOT Approval: 49 CFR <u>§178.273</u>, <u>§178.274</u>, <u>§178.275</u>

CSC Approval Reference: <u>USA/AB-119/22</u>
Customs Approval Reference: <u>USA/IMO/AB/119/22</u>
Customs Approval Reference: <u>USA/119-AB/22</u>
International Union of Railways (UIC): <u>IRS 50592</u>
Other(s): <u>TC, ISO 668, 1161, 6346, 1496-3</u>

IMDG Approval Reference: <u>USA/IMO/AB/119/22</u>
Sec. 6.7 ADR/RID Approval Number: <u>NL/AB-119/22</u>
US DoT SP: <u>N/A</u> and/or TC Equiv.Cert.: <u>N/A</u>

CONTAINER CHARACTERISTICS

ISO Size/Type Code: 22K2

Maximum Operating Gross Mass: 36000 kg Tare: 3610 kg Max. Permissible Payload: 32390 kg

Allowable Stacking Load for 1.8 g: <u>213360</u> kg Transverse Racking Test Force: <u>150000</u> newtons

TANK CHARACTERISTICS

Design Code: <u>ASME BPVC.VIII.1 & EN 14025</u> Liquid Capacity at 20°C: <u>25010</u> liters (total)

Overall Tank Length: 6009 mm Outside Tank Diameter: 2389 mm

Head Matl Spec.: SANS 50028-7:1.4402 Head Thickness: 4.6 mm (as built after forming) Head Corrosion Allowance: 0.3 mm

Shell Matl Spec.: SANS 50028-7:1.4402 Shell Thickness: 4.6 mm (as built) Shell Corrosion Allowance: 0.42 mm

Equiv. Reference Steel Thickness: 6 mm

MAWP: 4 bar MAWP of Heating System: 4 bar

External Design Pressure: 0.41 bar

Design Temperature Range: Min.: 40 °C; Max.: 130 °C

Design Temperature Range: Min.: -40 °C; Max.: 130 °C

Coating/Lining: Type: N/A & Thickness: N/A mm

Baffles: N/A Quantity: N/A

Cladding: Type: GRP & Thickness: 1.8/2.0 mm

Discharge: Bottom

Bottom Discharge No. of Closures in Series: Enter

PRESSURE RELIEF DEVICES

1st; Quantity: <u>1</u> 2nd; Quantity: <u>---</u> 3rd; Quantity: <u>---</u> ---

Total Capacity: 3.922 m³/s
SERVICE EQUIPMENT

Fort Vale 3" Bottom Discharge, 1.5" Air line, 3" Top Discharge Provision

TESTING INFORMATION

Prototype Test Certificate: SQ5160305-A, dated: 12-Mar-2022 Rail Impact Test Certificate/Report: SQ5038404-A, dated: 21-Jan-2022

TC Impact Approved: Yes

PRESSURE TEST

Test Pressure of Tank: 6 bar, dated: 07-Apr-2022 Test Pressure of Heating System: 6 bar, dated: 05-Apr-2022

Leak Proof Test of Container: <u>1</u> bar, dated: <u>08-Apr-2022</u>

Approved Commodities: Compatibilities commodities as per T11 / L4BN

Portable Tank Instruction: T11 ADR/RID Tank Code: L4BN

Marking: 07/04/2022 P

Stamping tank-plate Next Inspection Date: 10/2024

Additional Information/Comments: The compatibilities between commodities and service equipment/pressure relief devices/vessel/gaskets are the responsibility of the

CSC Plate Stamping Date: 04/2022 or ACEP Nº.: N/A

Field Office: ABS Shanghai

owner. Shipping name/special provisions markings are the responsibility of the owner.

Issued on: 15-Apr-2022 at Jingjiang, Jiangsu, China by Shen, Songxian (Empl. No. 7121)

Request Reviewed and NO Conflict of Interest Identified.

This Certificate evidences compliance with one or more of the Rules, guides, standards, or other characters, it Aber can Bureau of Shipping and is issued solely for the use of the Bureau, its committees, its clients or other authorized entities. This Certificate is a representation only that the conference of the presentation of the presentatio

CNT-SFM-00058 Revision 4 Page 1 of 1