

## American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Certificate Nº: SQ5236463-81

Owner No.: FLNU 501756-2

Owner FALCON LEASE PTE LTD.

& address 60 PAYA LEBAR ROAD, #12-05, PAYA LEBAR SQUARE, SINGAPORE, 409051

Manufacturer <u>JINGJIANG ASIAN-PACIFIC LOGISTICS EQUIPMENT CO., LTD</u> & address <u>NO. 199 XINGANG AVENUE, JINGJIANG, CHINA, 214500</u> Serial No.: <u>2202469</u>

Manufacturer's Model Nº.: A023E-025-0003

**APPLICABLE RULES, REGULATIONS AND STANDARDS** 

ABS Design Type №: <u>AB/119/22</u> US DOT Identification Code: <u>IA-8101</u>

ABS Approval Ref. №: <u>T2232130</u> US DOT Approval: 49 CFR <u>§178.273</u>, <u>§178.274</u>, <u>§178.275</u>,

CSC Approval Reference: USA/AB-119/22

Customs Approval Reference: USA/IMO/AB/119/22

Customs Approval Reference: USA/I19-AB/22

Sec. 6.7 ADR/RID Approval Number: NL/AB-119/22

International Union of Railways (UIC): IRS 50592

Other(s): TC, ISO 668, 1161, 6346, 1496-3

US Dot SP: N/A and/or TC Equiv.Cert.: N/A

**CONTAINER CHARACTERISTICS** 

ISO Size/Type Code: 22K2

Overall Length: <u>6058</u> mm Height <u>2591</u> mm

Maximum Operating Gross Mass: 36000 kg Tare: 3610 kg Max. Permissible Payload: 32390 kg

Allowable Stacking Load for 1.8 g: <u>213360</u> kg Transverse Racking Test Force: <u>150000</u> newtons

TANK CHARACTERISTICS

Design Code: <u>ASME BPVC.VIII.1 & EN 14025</u> Liquid Capacity at 20°C: <u>25000</u> liters (total)

Overall Tank Length: 6009 mm Outside Tank Diameter: 2389 mm

Head Matl Spec.: SANS 50028-7:1.4402 Head Thickness: 4.6 mm (as built after forming) Head Corrosion Allowance: 0.3 mm

Shell Matl Spec.: SANS 50028-7:1.4402 Shell Thickness: 4.6 mm (as built) Shell Corrosion Allowance: 0.42 mm

Equiv. Reference Steel Thickness: 6 mm

MAWP: 4 bar MAWP of Heating System: 4 bar

External Design Pressure: <u>0.41</u> bar Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C

Coating/Lining: Type: N/A & Thickness: N/A mm

Baffles: N/A Quantity: N/A

Cladding: Type: GRP & Thickness: 1.8/2.0 mm

Discharge: Bottom

Bottom Discharge No. of Closures in Series: Enter

PRESSURE RELIEF DEVICES

1<sup>st</sup>; Quantity: <u>1</u> 2<sup>nd</sup>; Quantity: <u>---</u> 3<sup>rd</sup>; Quantity: <u>---</u>

 Manufacturer
 Fort Vale
 -- -- 

 Catalog Number
 010/144000
 -- -- 

 Set Pressure
 4.4 bar
 -- bar

 Rupture
 N/A bar
 -- bar

 Capacity (each)
 3.922 m³/s
 -- m³/s

Total Capacity: 3.922 m<sup>3</sup>/s

SERVICE EQUIPMENT

Fort Vale 3" Bottom Discharge, 1.5" Air line, 3" Top Discharge Provision

**TESTING INFORMATION** 

Prototype Test Certificate: SQ5160305-A, dated: 12-Mar-2022 Rail Impact Test Certificate/Report: SQ5038404-A, dated: 21-Jan-2022

TC Impact Approved: Yes

PRESSURE TEST

Test Pressure of Tank: 6 bar, dated: 09-Apr-2022 Test Pressure of Heating System: 6 bar, dated: 07-Apr-2022

Leak Proof Test of Container: 1 bar, dated: 12-Apr-2022

Approved Commodities: Compatibilities commodities as per T11 / L4BN

Portable Tank Instruction: <u>T11</u> ADR/RID Tank Code: <u>L4BN</u>

Marking: 09/04/2022 P A

CSC Plate Stamping Date: <u>04/2022</u> or ACEP Nº.: <u>N/A</u>

Stamping tank-plate Next Inspection Date: 10/2024

Additional Information/Comments: The compatibilities between commodities and service equipment/pressure relief devices/vessel/gaskets are the responsibility of the

owner. Shipping name/special provisions markings are the responsibility of the owner.

Issued on: 15-Apr-2022 at Jingjiang, Jiangsu, China by Shen, Songxian (Empl. No. 7121)

Field Office: ABS Shanghai

Request Reviewed and NO Conflict of Interest Identified.

TE: This Certificate evidences compliance with one or more of the Rules, guides, standards, or other orterial committees, its clients or other authorized entities. This Certificate is a representation only that the contain (the straight erein has been found to comply with one or more of the Rules, guides, standards, or other criteria of American Bureau of Shipping. The validity, applicability and interpretation is the Sertificate is governed by the Rules and standards of American Bureau of Shipping who shall remain the sole judge thereof. Nothing contained in this Certificate or in any Reponsisting in contemplation of this Certificate shall be deemed to relieve any designer, builder, owner, manufacturer, seller, supplier, repairer, operator, or other entity of any warranty express or implied.

CNT-SFM-00058 Revision 4 Page 1 of 1