

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

	ALCON LEASE PTE LTD. 0 PAYA LEBAR ROAD, #12-05, PAYA LEBA	R SQUARE, SINGAPORE, 40905'	Owner No.: <u>FLNU 501765-0</u>
Manufacturer <u>J</u>	60 PAYA LEBAR ROAD, #12-05, PAYA LEBAR SQUARE, SINGAPORE, 409051 Owner Not. <u>FLNO 501705-0</u> JINGJIANG ASIAN-PACIFIC LOGISTICS EQUIPMENT CO., LTD Serial Not.: 2202478		
	IO. 199 XINGANG AVENUE, JINGJIANG, CH	<u>HNA, 214500</u>	<u></u>
Manufacturer's Model Nº.: A023E-025	<u></u>		
APPLICABLE RULES, REGULATIO	NS AND STANDARDS		
ABS Design Type №: <u>AB/119/22</u>		US DOT Identification Code: IA-8	3101
ABS Approval Ref. №: <u>T2232130</u>		US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>	
CSC Approval Reference: USA/AB-119/22		IMDG Approval Reference: USA/IMO/AB/119/22	
Customs Approval Reference: USA/119-AB/22		Sec. 6.7 ADR/RID Approval Num	
International Union of Railways (UIC): <u>IRS 50592</u>		Sec. 6.8 ADR/RID Approval Number: <u>NL/AB-119/22</u>	
Other(s): TC, ISO 668, 1161, 6346, 14	496-3	US DoT SP: <u>N/A</u> and/or TC Equiv	v.Cert.: <u>N/A</u>
CONTAINER CHARACTERISTICS			
ISO Size/Type Code: 22K2	10/i-di	b. 2420 mm	Unight 2504 mm
Overall Length: <u>6058</u> mm Maximum Operating Gross Mass: 26 0		th: <u>2438</u> mm re: <u>3610</u> kg	Height <u>2591</u> mm Max. Permissible Payload: <u>32390</u> kg
Maximum Operating Gross Mass: <u>360</u> Allowable Stacking Load for 1.8 g: <u>213</u>		Transverse Racking Test Force:	
TANK CHARACTERISTICS	5000 kg	Transverse Racking rest Force.	Terrens
Design Code: ASME BPVC.VIII.1 & E	EN 14025	Liquid Capacity at 20°C: 25000 lit	ters (total)
Overall Tank Length: 6009 mm		Outside Tank Diameter: 2389 mn	
Head Matl Spec.: SANS 50028-7:1.44	Head Thickness: <u>4.6</u> mr		Head Corrosion Allowance: 0.3 mm
Shell Matl Spec.: <u>SANS 50028-7:1.44</u>			Shell Corrosion Allowance: 0.42 mm
Equiv. Reference Steel Thickness: 6 r			
MAWP: <u>4</u> bar		MAWP of Heating System: 4 bar	
External Design Pressure: 0.41 bar		Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C	
Coating/Lining: Type: N/A & Thicknes	pe: <u>N/A</u> & Thickness: <u>N/A</u> mm Insulation: Type: <u>Rockwool</u> & Thickness: <u>50</u> mm		ckness: <u>50</u> mm
Baffles: <u>N/A</u> Quantity: <u>N/A</u>		Cladding: Type: <u>GRP</u> & Thickness: <u>1.8/2.0</u> mm	
Discharge: Bottom		Bottom Discharge No. of Closure	s in Series: <u>Enter</u>
PRESSURE RELIEF DEVICES			
	st ; Quantity: <u>1</u>	2 nd ; Quantity:	3 rd ; Quantity:
_	ort Vale		
-	<u>10/144000</u> . <u>4</u> bar	bar	bar
	<u>I/A</u> bar	bar	bar
	<u>.922</u> m ³ /s	<u> </u>	<u> </u>
Total Capacity: <u>3.922</u> m ³ /s			
SERVICE EQUIPMENT			
Fort Vale 3" Bottom Discharge, 1.5" A	Air line, <u>3" Top Discharge Provision</u>		
TESTING INFORMATION			
Prototype Test Certificate: SQ516030	5-A, dated: <u>12-Mar-2022</u>	Rail Impact Test Certificate/Repo	ort: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>
TC Impact Approved: <u>Yes</u>			
PRESSURE TEST			
Test Pressure of Tank: 6 bar, dated: 0)8-Apr-2022	Test Pressure of Heating System	:: <u>6</u> bar, dated: <u>07-Apr-2022</u>
Leak Proof Test of Container: 1 bar, d	lated: 09-Apr-2022		
Approved Commodities: Compatibilitie	es commodities as per T11 / L4BN		
Portable Tank Instruction: T11		ADR/RID Tank Code: L4BN	
Marking: 08/04/2022 P B		CSC Plate Stamping Date: <u>04/2022</u> or ACEP Nº.: <u>N/A</u>	
Stamping tank-plate		Next Inspection Date: 10/2024	
	e compatibilities between commodities and se	ervice equipment/pressure relief de	vices/vessel/gaskets are the responsibility of the
owner. Shipping name/special provision	ons markings are the responsibility of the owr	ner.	
issued on: <u>15-Apr-2022</u> at <u>Jingjiang, J</u>	<u> Jiangsu, China</u> by <u>Shen, Songxian</u> (Empl. No.		Field Office: ABS Shanghai
NOTE: This Certificate evidences complian committees, its clients or other auth	(<	or other criterine American Byreau of S	Shipping and is issued solely for the use of the Bureau, its has been found to comply with one or more of the Rules, soverned by the Rules and standards of American Bureau
or Shipping who shall remain the sol	f American Bureau of Shipping. The validity, applicab le judge thereof. Nothing contained in this Certificate , supplier, repairer, operator, or other entity of any wa	or in any Report issues in come inplation	s governed by the Rules and standards of American Bureau of this Certificate shall be deemed to relieve any designer