

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

	SE PTE LTD. AR ROAD, #12-05, PAYA LEBAR SQUARE, SINGAPORE, 409051 Owner No.: FLNU 501767-0
Manufacturer JINGJIANG	SIAN-PACIFIC LOGISTICS EQUIPMENT CO., LTD Serial No.: 2202480
	ANG AVENUE, JINGJIANG, CHINA, 214500
Manufacturer's Model №.: <u>A023E-025-0003</u>	
APPLICABLE RULES, REGULATIONS AND ST	ANDARDS
ABS Design Type №: <u>AB/119/22</u>	US DOT Identification Code: <u>IA-8101</u>
ABS Approval Ref. Nº: T2232130	US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>
CSC Approval Reference: USA/AB-119/22	IMDG Approval Reference: USA/IMO/AB/119/22
Customs Approval Reference: USA/119-AB/22	Sec. 6.7 ADR/RID Approval Number: <u>NL/AB-119/22</u>
International Union of Railways (UIC): IRS 50592	Sec. 6.8 ADR/RID Approval Number: NL/AB-119/22
Other(s): <u>TC, ISO 668, 1161, 6346, 1496-3</u>	US DoT SP: <u>N/A</u> and/or TC Equiv.Cert.: <u>N/A</u>
ISO Size/Type Code: 22K2	Width: 2420 mm
Overall Length: 6058 mm Maximum Operating Gross Mass: 36000 kg	Width: 2438 mm Height 2591 mm Tare: 3610 kg Max. Permissible Payload: 32390 kg
Allowable Stacking Load for 1.8 g: 213360 kg	Transverse Racking Test Force: <u>150000</u> newtons
TANK CHARACTERISTICS	
Design Code: ASME BPVC.VIII.1 & EN 14025	Liquid Capacity at 20ºC: <u>24980</u> liters (total)
Overall Tank Length: 6009 mm	Outside Tank Diameter: 2389 mm
Head Matl Spec.: <u>SANS 50028-7:1.4402</u>	Head Thickness: <u>4.6</u> mm (as built after forming) Head Corrosion Allowance: <u>0.3</u> mm
Shell Matl Spec.: <u>SANS 50028-7:1.4402</u>	Shell Thickness: <u>4.6</u> mm (as built) Shell Corrosion Allowance: <u>0.42</u> mm
Equiv. Reference Steel Thickness: 6 mm	
MAWP: <u>4</u> bar	MAWP of Heating System: <u>4</u> bar
External Design Pressure: 0.41 bar	Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C
Coating/Lining: Type: N/A & Thickness: N/A mm	Insulation: Type: Rockwool & Thickness: 50 mm
Baffles: <u>N/A</u> Quantity: <u>N/A</u>	Cladding: Type: <u>GRP</u> & Thickness: <u>1.8/2.0</u> mm
Discharge: Bottom	Bottom Discharge No. of Closures in Series: Enter
PRESSURE RELIEF DEVICES	
1 st ; Quantity:	
Manufacturer <u>Fort Vale</u>	
Catalog Number010/144000Set Pressure4.4 bar	
Set Pressure <u>4.4</u> barRuptureN/A bar	bar bar bar bar
Capacity (each) <u>3.922</u> m ³ /s	<u></u> bai m ³ /s m ³ /s
Total Capacity: <u>3.922</u> m ³ /s	
Fort Vale 3" Bottom Discharge, 1.5" Air line, 3" T	p Discharge Provision
Prototype Test Certificate: SQ5160305-A, dated:	2-Mar-2022 Rail Impact Test Certificate/Report: SQ5038404-A, dated: 21-Jan-2022
TC Impact Approved: <u>Yes</u>	
PRESSURE TEST	
Test Pressure of Tank: 6 bar, dated: 08-Apr-2022	Test Pressure of Heating System: <u>6</u> bar, dated: <u>07-Apr-2022</u>
Leak Proof Test of Container: <u>1</u> bar, dated: <u>11-Ap</u>	
Approved Commodities: Compatibilities commodi	
Portable Tank Instruction: T11	ADR/RID Tank Code: <u>L4BN</u>
Marking: 08/04/2022 P	CSC Plate Stamping Date: <u>04/2022</u> or ACEP №.: <u>N/A</u>
Marking: UO/U4/ZUZZ F Stamping tank-plate	Next Inspection Date: <u>10/2024</u>
	ies between commodities and service equipment/pressure relief devices/vessel/gaskets are the responsibility of the
owner. Shipping name/special provisions marking	are the responsibility of the owner.
Issued on: <u>15-Apr-2022</u> at <u>Jingjiang, Jiangsu, Chi</u>	a by Shen, Songxian (Empl. No. 7121)
Request Reviewed and <u>NO</u> Conflict of Interest Id	ntified.
of Snipping who shall remain the sole judge there	more of the Rules, guides, standards, or other criteries to medican Bureau of Shipping and is issued solely for the use of the Bureau, in This Certificate is a representation only that the Consult. An associated herein has been found to comply with one or more of the Rules eau of Shipping. The validity, applicability and interpretative antibility entities certificate is governed by the Rules and standards of American Burea f. Nothing contained in this Certificate or in any Report saved in contemplation of this Certificate shall be deemed to relieve any designe rer, operator, or other entity of any warranty express of implied.