

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

	<u>CON LEASE PTE LTD.</u> AYA LEBAR ROAD. #12-05. PAYA LEBAI	R SQUARE, SINGAPORF 4090	51 Owner No.: <u>FLNU 501768-6</u>
Manufacturer <u>JINC</u>	60 PAYA LEBAR ROAD, #12-05, PAYA LEBAR SQUARE, SINGAPORE, 409051 Owner Not. <u>FLIVE 301708-0</u> JINGJIANG ASIAN-PACIFIC LOGISTICS EQUIPMENT CO., LTD Serial No.: 2202481		
	199 XINGANG AVENUE, JINGJIANG, CH	INA, 214500	<u></u>
Manufacturer's Model Nº.: A023E-025-00			
APPLICABLE RULES, REGULATIONS	AND STANDARDS		
ABS Design Type №: <u>AB/119/22</u>		US DOT Identification Code: IA	-8101
ABS Approval Ref. Nº: <u>T2232130</u>		US DOT Approval: 49 CFR §17	<u>8.273. §178.274. §178.275</u>
CSC Approval Reference: USA/AB-119/2	22	IMDG Approval Reference: USA	A/IMO/AB/119/22
Customs Approval Reference: USA/119-		Sec. 6.7 ADR/RID Approval Nu	
International Union of Railways (UIC): IR		Sec. 6.8 ADR/RID Approval Number: <u>NL/AB-119/22</u>	
Other(s): <u>TC, ISO 668, 1161, 6346, 1496</u>	-3	US DoT SP: <u>N/A</u> and/or TC Equ	Jiv.Cert.: <u>N/A</u>
CONTAINER CHARACTERISTICS			
ISO Size/Type Code: <u>22K2</u>	VA/Selat	0420 mm	Light 2504 mm
Overall Length: 6058 mm		n: <u>2438</u> mm e: <u>3610</u> kg	Height <u>2591</u> mm Max. Permissible Payload: <u>32390</u> kg
Maximum Operating Gross Mass: <u>36000</u> Allowable Stacking Load for 1.8 g: <u>21336</u>		Transverse Racking Test Force	
TANK CHARACTERISTICS		Transverse Racking rest roree	
Design Code: ASME BPVC.VIII.1 & EN	14025	Liquid Capacity at 20°C: 25040	liters (total)
Overall Tank Length: 6009 mm		Outside Tank Diameter: 2389 n	
Head Matl Spec.: <u>SANS 50028-7:1.4402</u>	Head Thickness: <u>4.6</u> mm		Head Corrosion Allowance: 0.3 mm
Shell Matl Spec.: <u>SANS 50028-7:1.4402</u>	Shell Thickness: <u>4.6</u> mm		Shell Corrosion Allowance: 0.42 mm
Equiv. Reference Steel Thickness: <u>6</u> mm			
MAWP: <u>4</u> bar		MAWP of Heating System: 4 ba	ar
External Design Pressure: 0.41 bar		Design Temperature Range: M	in.: <u>-40</u> °C; Max.: <u>130</u> °C
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N</u>	<u>V/A</u> mm	Insulation: Type: Rockwool & Thickness: 50 mm	
Baffles: <u>N/A</u> Quantity: <u>N/A</u>		Cladding: Type: GRP & Thickne	ess: <u>1.8/2.0</u> mm
Discharge: Bottom		Bottom Discharge No. of Closu	res in Series: <u>Enter</u>
PRESSURE RELIEF DEVICES			
	Quantity: <u>1</u>	2 nd ; Quantity:	3 rd ; Quantity:
	Vale		
ő	<u>144000</u>		
Set Pressure4.4 tRuptureN/A		bar	<u></u> bar bar
	<u>2</u> m ³ /s	<u></u> bar m³/s	m ³ /s
Total Capacity: <u>3.922</u> m ³ /s			,0
SERVICE EQUIPMENT			
Fort Vale 3" Bottom Discharge, 1.5" Air I	ine, 3" Top Discharge Provision		
TESTING INFORMATION			
Prototype Test Certificate: SQ5160305-A	dated: 12-Mar-2022	Rail Impact Test Certificate/Rer	oort: SQ5038404-A, dated: 21-Jan-2022
TC Impact Approved: Yes			<u></u>
PRESSURE TEST			
Test Pressure of Tank: 6 bar, dated: 08-	Apr-2022	Test Pressure of Heating Syste	m: 6 bar, dated: 07-Apr-2022
Leak Proof Test of Container: <u>1</u> bar, date		and the second system	
Approved Commodities: Compatibilities of			
Portable Tank Instruction: T11		ADR/RID Tank Code: L4BN	
00/04/202	2 D B	CSC Plate Stamping Date: 04/2	2022 or ACEP №:: <u>N/A</u>
Marking: 08/04/202		Next Inspection Date: 10/2024	
Stamping tank-plate			
	ompatibilities between commodities and se markings are the responsibility of the own		levices/vessel/gaskets are the responsibility of the
	ngsu, China by Shen, Songxian (Empl. No.		Field Office: ABS Shanghai
Request Reviewed and <u>NO</u> Conflict of 1	Interest Identified.		
			}
NOTE: This Certificate evidences compliance v	with one or more of the Rules, guides, standards,	or other criter and Imerican Bureau c	Shipping and is issued solely for the use of the Bureau, its
of Snipping who shall remain the sole ju	ed entities. This Certificate is a representation or nerican Bureau of Shipping. The validity, applicabi dge thereof. Nothing contained in this Certificate oplier, repairer, operator, or other entity of any war	or in any Report squep in contemplation	Shipping and is issued solely for the use of the Bureau, its in has been found to comply with one or more of the Rules, is governed by the Rules and standards of American Bureau on of this Certificate shall be deemed to relieve any designer