

American Bureau of Shipping UN Portable Tank/Tank Container

Production Certificate

Owner & address	<u>FALCON LEASE</u> <u>60 PAYA LEBAR</u>	<u>PTE LTD.</u> ROAD, #12-05, PAYA LEBA	R SQUARE, SINGAPORE,	409051 Owner No.: FLNU 600430-1	
Manufacturer		JINGJIANG ASIAN-PACIFIC LOGISTICS EQUIPMENT CO., LTD. NO. 199 XINGANG AVENUE, JINGJIANG, CHINA, 214500 E. 036.0002			
& address Manufacturer's Model Nº.:					
	<u>A023E-028-0002</u>				
APPLICABLE RULES, RE	EGULATIONS AND STAN	DARDS			
ABS Design Type №: <u>AB/′</u>	124/22		US DOT Identification Cod	de: <u>IA-8101</u>	
ABS Approval Ref. №: <u>T2212896 / T2225906</u>			US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>		
CSC Approval Reference: USA/AB-124/22			IMDG Approval Reference: USA/IMO/AB/124/22		
Customs Approval Reference: USA/124-AB/22			Sec. 6.7 ADR/RID Approval Number: NL/AB-124/22		
International Union of Railways (UIC): <u>IRS 50592</u> Other(s): <u>TC, ISO 668, 1161, 6346, 1496-3</u>			Sec. 6.8 ADR/RID Approval Number: <u>NL/AB-124/22</u> US DoT SP: <u>N/A</u> and/or TC Equiv.Cert.: <u>N/A</u>		
			US DOT SP: <u>N/A</u> and/or T	C Equiv.Cert.: <u>N/A</u>	
CONTAINER CHARACTE					
SO Size/Type Code: <u>22K2</u> Overall Length: <u>6058</u> mm	<u> </u>	Widt	h: 2438 mm	Height <u>2591</u> mm	
Maximum Operating Gross Mass: <u>36000</u> kg			e: <u>3760</u> kg	Max. Permissible Payload: <u>32240</u> kg	
Allowable Stacking Load for 1.8 g: 213360 kg			Transverse Racking Test I		
ANK CHARACTERISTIC					
esign Code: <u>ASME BPV</u>			Liquid Capacity at 20°C: 2	5980 liters (total)	
Overall Tank Length: <u>6029</u> mm			Outside Tank Diameter: 24		
lead Matl Spec.: SANS 50		Head Thickness: 4.6 mm	(as built after forming)	Head Corrosion Allowance: 0.2 mm	
Shell Matl Spec.: SANS 50	0028-7:1.4402	Shell Thickness: 4.6 mm	(as built)	Shell Corrosion Allowance: 0.42 mm	
quiv. Reference Steel Th	ickness: <u>6</u> mm				
/AWP: <u>4</u> bar			MAWP of Heating System: <u>4</u> bar		
External Design Pressure: 0.41 bar			Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C		
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm			Insulation: Type: Rockwool & Thickness: 50 mm		
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: <u>GRP</u> & Thickness: <u>1.8/2.0</u> mm		
Discharge: <u>Bottom</u>			Bottom Discharge No. of C	Closures in Series: <u>3</u>	
PRESSURE RELIEF DEV					
	1 st ; Quantity: <u>1</u>		2 nd ; Quantity:	3 rd ; Quantity:	
Manufacturer	Perolo		=		
Catalog Number	MX65F44TSP			=	
Set Pressure Rupture	<u>4.4</u> bar <u>N/A</u> bar		<u></u> bar bar	<u></u> bar bar	
Capacity (each)	<u>4.032</u> m ³ /s		<u></u> m ³ /s	<u></u> m ³ /s	
otal Capacity: <u>4.032</u> m ³ /s					
	1				
	ge, 1.5" Air Line, 3" Top Dis	charge Provision			
ESTING INFORMATION		in anger renderin			
	<u>SQ5160313-A, dated: 09-N</u>	Mar-2022	Rail Impact Test Certificat	e/Report: SQ5038404-A, dated: 21-Jan-2022	
C Impact Approved: Yes			rtail impact root conmout	<u> </u>	
RESSURE TEST					
Test Pressure of Tank: <u>6</u> bar, dated: <u>17-Mar-2022</u>			Test Pressure of Heating	System: 6 bar, dated: 15-Mar-2022	
_	ner: 1 bar, dated: 22-Mar-20)22	rest ressure of richting t	5951011. <u>0</u> 541, 44164. <u>10 1441 2022</u>	
	compatibilities commodities				
Portable Tank Instruction:			ADR/RID Tank Code: L4B	N	
		ר		_	
Marking: 17/0	<u>3/2022 P</u> A	5	USU Flate Stamping Date	: <u>03/2027</u> or ACEP №.: <u>N/A</u>	
Stamping			Next Inspection Date: 09/2	2024	
Additional Information/Con	nments: The compatibilities			elief devices/vessel/gaskets are the responsibility of the	
wner. Shipping name/spe	ecial provisions markings ar	e the responsibility of the own	er.		
ssued on: <u>24-Mar-2022</u> at	t <u>Jingjiang, Jiangsu, China</u>	by <u>Shen, Songxian</u> (Empl. No.		Field Office: ABS Shangh	
Request Reviewed and	NO Conflict of Interest Identi	fied.			
DTE: This Certificate eviden committees, its clients	ces compliance with one or more or other authorized entities. The	re of the Rules, guides, standards, is Certificate is a representation or	or other criter of American By	reau of Shipping and is issued solely for the use of the Bureau, d herein has been found to comply with one or more of the Rul	
guides, standards, or o of Shipping who shall r	other criteria of American Bureau remain the sole judge thereof. N	of Shipping. The validity, applicabi othing contained in this Certificate	lity and interpretential or the Cert or in any Report issued in conte	reau of Shipping and is issued solely for the use of the Bureau, d hyrein has been found to comply with one or more of the Rul itificate is governed by the Rules and standards of American Bure inplation of this Certificate shall be deemed to relieve any design	
builder, owner, manufa	acturer, seller, supplier, repairer,	operator, or other entity of any wa	rranty express or implied.		
IT-SEM-00058		Po	vision 3	Page 1 o	