

## American Bureau of Shipping UN Portable Tank/Tank Container Production Certificate

Dwner address	FALCON LEASE PTE LT 60 PAYA LEBAR ROAD,	<u>D.</u> #12-05, PAYA LEBAR SQUARE, SINGAPORE,	409051 Owner No.: FLNU 600437-0	
lanufacturer		JINGJIANG ASIAN-PACIFIC LOGISTICS EQUIPMENT CO., LTD.		
address		NO. 199 XINGANG AVENUE, JINGJIANG, CHINA, 214500 Serial No.: 2202685		
lanufacturer's Model Nº.: A0	<u>23E-026-0002</u>			
PPLICABLE RULES, REG	JLATIONS AND STANDARDS			
BS Design Type №: <u>AB/124</u>	/22	US DOT Identification Cod	de: IA-8101	
ABS Approval Ref. Nº: T2212896 / T2225906		US DOT Approval: 49 CF	US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>	
CSC Approval Reference: USA/AB-124/22		IMDG Approval Reference	IMDG Approval Reference: USA/IMO/AB/124/22	
Customs Approval Reference: USA/124-AB/22		Sec. 6.7 ADR/RID Approv	Sec. 6.7 ADR/RID Approval Number: NL/AB-124/22	
International Union of Railways (UIC): IRS 50592		Sec. 6.8 ADR/RID Approv	/al Number: <u>NL/AB-124/22</u>	
Other(s): <u>TC, ISO 668, 1161,</u>	<u>6346, 1496-3</u>	US DoT SP: <u>N/A</u> and/or T	C Equiv.Cert.: <u>N/A</u>	
ONTAINER CHARACTERI	STICS			
SO Size/Type Code: 22K2				
Overall Length: 6058 mm		Width: <u>2438</u> mm	Height <u>2591</u> mm	
Aaximum Operating Gross M		Tare: <u>3760</u> kg	Max. Permissible Payload: <u>32240</u> kg	
Ilowable Stacking Load for 1	.8 g: <u>213360</u> kg	Transverse Racking Test	Force: <u>150000</u> newtons	
Design Code: <u>ASME BPVC.V</u>		Liquid Capacity at 20°C: 2		
Overall Tank Length: 6029 m		Outside Tank Diameter: <u>2</u>		
lead Matl Spec.: <u>SANS 5002</u> Shell Matl Spec.: <u>SANS 5002</u>		d Thickness: <u>4.6</u> mm (as built after forming) Il Thickness: 4.6 mm (as built)	Head Corrosion Allowance: 0.2 mm Shell Corrosion Allowance: 0.42 mm	
equiv. Reference Steel Thick		in Thickness. <u>4.0</u> min (as built)	Shell Consider Allowance. 0.42 milli	
/AWP: <u>4</u> bar	1000. <u>0</u> mm	MAWP of Heating System	n: 4 bar	
External Design Pressure: 0.4	11 bar		Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C	
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm			Insulation: Type: Rockwool & Thickness: 50 mm	
Baffles: <u>N/A</u> Quantity: <u>N/A</u>		Cladding: Type: <u>GRP</u> & T	Cladding: Type: GRP & Thickness: <u>1.8/2.0</u> mm	
Discharge: Bottom			Bottom Discharge No. of Closures in Series: 3	
RESSURE RELIEF DEVICE	S			
	1 <sup>st</sup> ; Quantity: <u>1</u>	2 <sup>nd</sup> ; Quantity:	3 <sup>rd</sup> ; Quantity:	
lanufacturer	Perolo			
Catalog Number	MX65F44TSP			
Set Pressure	<u>4.4</u> bar	<u></u> bar	<u></u> bar	
Rupture	<u>N/A</u> bar	<u></u> bar	<u></u> bar	
Capacity (each)	<u>4.032</u> m <sup>3</sup> /s	<u></u> m³/s	<u></u> m <sup>3</sup> /s	
otal Capacity: <u>4.032</u> m <sup>3</sup> /s				
	1.5" Air Line, 3" Top Discharge I	Provision		
ESTING INFORMATION				
Prototype Test Certificate: <u>SQ5160313-A</u> , dated: <u>09-Mar-2022</u>		Rail Impact Test Certificat	Rail Impact Test Certificate/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>	
C Impact Approved: <u>Yes</u>				
RESSURE TEST				
est Pressure of Tank: <u>6</u> bar,		Test Pressure of Heating	System: <u>6</u> bar, dated: <u>14-Mar-2022</u>	
eak Proof Test of Container:				
· · · · · · · · · · · · · · · · · · ·	patibilities commodities as per T			
Portable Tank Instruction: T11		ADR/RID Tank Code: L4E	ADR/RID Tank Code: <u>L4BN</u>	
Marking: <u>15/03/2022 P</u> <i>B</i>		CSC Plate Stamping Date	CSC Plate Stamping Date: <u>03/2027</u> or ACEP №.: <u>N/A</u>	
Stamping tan		Next Inspection Date: 09/2	2024	
dditional Information/Comm	ents: The compatibilities between		elief devices/vessel/gaskets are the responsibility of th	
wner. Shipping name/specia	I provisions markings are the res	ponsibility of the owner.		
	ngjiang, Jiangsu, China by <u>Shen</u> ,		Field Office: ABS Shangh	
	Conflict of Interest Identified.		<u> </u>	
Request Reviewed and NO				
			rear of Shipping and is issued solely for the use of the Bureau and rerein has been found to comply with one or more of the Ru micrates governed by the Rules and standards of American Bur mplaton of this Certificate shall be deemed to relieve any design	