

American Bureau of Shipping UN Portable Tank/Tank Container

Production Certificate

FALCON LEASE PTE LTD. Owner Owner No.: FLNU 600440-4 & address 60 PAYA LEBAR ROAD, #12-05, PAYA LEBAR SQUARE, SINGAPORE, 409051 JINGJIANG ASIAN-PACIFIC LOGISTICS EQUIPMENT CO., LTD. Manufacturer Serial No.: 2202688 & address NO. 199 XINGANG AVENUE, JINGJIANG, CHINA, 214500 Manufacturer's Model Nº .: A023E-026-0002 APPLICABLE RULES, REGULATIONS AND STANDARDS ABS Design Type Nº: AB/124/22 US DOT Identification Code: IA-8101 ABS Approval Ref. Nº: T2212896 / T2225906 US DOT Approval: 49 CFR §178.273, §178.274, §178.275 CSC Approval Reference: USA/AB-124/22 IMDG Approval Reference: USA/IMO/AB/124/22 Customs Approval Reference: USA/124-AB/22 Sec. 6.7 ADR/RID Approval Number: NL/AB-124/22 International Union of Railways (UIC): IRS 50592 Sec. 6.8 ADR/RID Approval Number: NL/AB-124/22 US DoT SP: N/A and/or TC Equiv.Cert.: N/A Other(s): TC, ISO 668, 1161, 6346, 1496-3 CONTAINER CHARACTERISTICS ISO Size/Type Code: 22K2 Overall Length: 6058 mm Width: 2438 mm Height 2591 mm Maximum Operating Gross Mass: 36000 kg Tare: 3760 kg Max. Permissible Payload: 32240 kg Transverse Racking Test Force: 150000 newtons Allowable Stacking Load for 1.8 g: 213360 kg TANK CHARACTERISTICS Design Code: ASME BPVC.VIII.1 & EN 14025 Liquid Capacity at 20°C: 25960 liters (total) Overall Tank Length: 6029 mm Outside Tank Diameter: 2423 mm Head Matl Spec .: SANS 50028-7:1.4402 Head Thickness: 4.6 mm (as built after forming) Head Corrosion Allowance: 0.2 mm Shell Matl Spec .: SANS 50028-7:1.4402 Shell Thickness: 4.6 mm (as built) Shell Corrosion Allowance: 0.42 mm Equiv. Reference Steel Thickness: 6 mm MAWP: 4 bar MAWP of Heating System: 4 bar External Design Pressure: 0.41 bar Design Temperature Range: Min.: -40 °C; Max.: 130 °C Coating/Lining: Type: N/A & Thickness: N/A mm Insulation: Type: Rockwool & Thickness: 50 mm Baffles: N/A Quantity: N/A Cladding: Type: GRP & Thickness: 1.8/2.0 mm Bottom Discharge No. of Closures in Series: 3 Discharge: Bottom PRESSURE RELIEF DEVICES 1st; Quantity: 1 2nd; Quantity: _---3rd; Quantity: _---Manufacturer Perolo MX65F44TSP Catalog Number ----Set Pressure 4.4 bar --- bar --- bar N/A bar Rupture --- bar --- bar ---- m³/s Capacity (each) 4.032 m³/s Total Capacity: 4.032 m3/s SERVICE EQUIPMENT Perolo 3" Bottom Discharge, 1.5" Air Line, 3" Top Discharge Provision **TESTING INFORMATION** Prototype Test Certificate: SQ5160313-A, dated: 09-Mar-2022 Rail Impact Test Certificate/Report: SQ5038404-A, dated: 21-Jan-2022 TC Impact Approved: Yes PRESSURE TEST Test Pressure of Tank: 6 bar, dated: 16-Mar-2022 Test Pressure of Heating System: 6 bar, dated: 14-Mar-2022 Leak Proof Test of Container: 1 bar, dated: 17-Mar-2022 Approved Commodities: Compatibilities commodities as per T11 / L4BN Portable Tank Instruction: T11 ADR/RID Tank Code: L4BN <u>16/03/2022 P</u> //B CSC Plate Stamping Date: 03/2027 or ACEP №:: N/A Marking: Next Inspection Date: 09/2024 Stamping tank-plate Additional Information/Comments: The compatibilities between commodities and service equipment/pressure relief devices/vessel/gaskets are the responsibility of the

 owner. Shipping name/special provisions markings are the responsibility of the owner.

 Issued on: 24-Mar-2022 at Jingjiang, Jiangsu, China by Shen, Songxian (Empl. No. 7121)

 Request Reviewed and NO Conflict of Interest Identified.

NOTE: This Certificate evidences compliance with one or more of the Rules, guides, standards, or other crite of American Byreau of Shipping and is issued solely for the use of the Bureau, its committees, its clients or other authorized entities. This Certificate is a representation only that the Control of the presence of the Rules, guides, standards, or other criteria of American Bureau of Shipping and is issued solely for the use of the Rules, guides, standards, or other criteria of American Bureau of Shipping. The validity, applicability and iterpresence of the Certificate is governed by the Rules and standards of American Bureau of Shipping who shall remain the sole judge thereof. Nothing contained in this Certificate or in any Notor state of the plate of the shall be deemed to relieve any designer, builder, owner, manufacturer, seller, supplier, repairer, operator, or other entity of any warranty express or implied