

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	Falcon Lease Pte	<u>Ltd</u> ROAD, #12-05, PAYA LEBAI		Owner No.: FLNU 600858-6	
				<u>-,409051</u>	
Manufacturer & address		Jing Jiang Asian-Pacific Logistics Equipment Co., Ltd Serial No.: 2210601 No. 199 Xingang Avenue, JingJiang City, Jiangsu Province, China			
Manufacturer's Model Nº.: <u>Al</u>	023E-026-0002				
APPLICABLE RULES, REG	ULATIONS AND STAND	ARDS			
ABS Design Type №: <u>AB/12</u>	1/22		US DOT Identification C	code: <u>IA-8101</u>	
ABS Approval Ref. №: <u>T2382295</u>			US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>		
CSC Approval Reference: USA/AB-124/22		IMDG Approval Reference: USA/IMO/AB/124/22			
Customs Approval Reference: USA/124-AB/22			Sec. 6.7 ADR/RID Approval Number: NL/AB-124/22		
International Union of Railways (UIC): IRS 50592			Sec. 6.8 ADR/RID Approval Number: NL/AB-124/22		
Other(s): <u>TC, ISO 668, 1161</u>	6346, 1496-3		US DoT SP: <u>N/A</u> and/or	TC Equiv. Cert.: <u>N/A</u>	
CONTAINER CHARACTER	STICS				
SO Size/Type Code: 22K2					
Overall Length: 6058 mm		Width	n: <u>2438</u> mm	Height <u>2591</u> mm	
Maximum Operating Gross N	lass: <u>36000</u> kg	Tar	e: <u>3760</u> kg	Max. Permissible Payload: 32240 kg	
Allowable Stacking Load for	1.8 g: <u>216000</u> kg		Transverse Racking Tes	st Force: <u>150000</u> newtons	
TANK CHARACTERISTICS					
esign Code: ASME BPVC VIII Div. 1 & EN 14025		Liquid Capacity at 20°C: 25970 liters (total)			
Overall Tank Length: 6029 m			Outside Tank Diameter:		
Head Matl Spec.: SANS 500		Head Thickness: 4.6 mm		Head Corrosion Allowance: 0.2 mm	
Shell Matl Spec.: SANS 5002		Shell Thickness: <u>4.6</u> mm	(as built)	Shell Corrosion Allowance: 0.42 mm	
Equiv. Reference Steel Thick	ness: <u>6</u> mm				
/IAWP: <u>4.0</u> bar			MAWP of Heating System: <u>4.0</u> bar		
External Design Pressure: <u>0.41</u> bar			Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C		
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm			Insulation: Type: <u>Rockwool</u> & Thickness: <u>50</u> mm		
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: <u>GRP</u> & Thickness: <u>1.8 / 2.0</u> mm Bottom Discharge No. of Closures in Series: <u>3</u>		
Discharge: <u>Bottom</u>			Bottom Discharge No. o	r Closures in Series: <u>3</u>	
PRESSURE RELIEF DEVIC			20d: Quantity: N/A	2rd: Quentity: N/A	
Manufacturer	1 st ; Quantity: <u>1</u> <u>GUARD</u>		2 nd ; Quantity: <u>N/A</u>	3 rd ; Quantity: <u>N/A</u>	
Catalog Number	AMF48001-00				
Set Pressure	<u>4.4</u> bar		 bar	 bar	
Rupture	<u>N/A</u> bar		<u></u> bar	bar	
Capacity (each)	4.67 m ³ /s		<u></u> m ³ /s	m³/s	
Total Capacity: <u>4.67</u> m ³ /s					
3" Bottom Discharge, 3" Top	Discharge Provision, 1.5	' Air line			
ESTING INFORMATION					
Prototype Test Certificate: S	25160313-A.R1, dated: 2	5-Mar-2022	Rail Impact Test Certific	cate/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>	
TC Impact Approved: Yes					
PRESSURE TEST					
Test Pressure of Tank: 6.0 bar, dated: 03-Jun-2023		Test Pressure of Heatin	g System: 6.0 bar, dated: 03-Jun-2023		
eak Proof Test of Container	· · · · · · · · · · · · · · · · · · ·	023		g e felenin <u>elle</u> sall, salesi, <u>el esti zeze</u>	
Approved Commodities: Con					
Portable Tank Instruction: T1			ADR/RID Tank Code: L	4 <u>BN</u>	
)			
Marking: 03/06	<u>5/2023</u> ₽ Æ	5	CSC Plate Stamping Da	ate: <u>06/2028</u> or ACEP Nº.: <u>N/A</u>	
			Next Inspection Date: 12	2/2025	
Stamping tar	-	1. A	· -		
		between commodities and se the responsibility of the own		e relief devices/vessel/gaskets are the responsibility of t	
ssued on: <u>09-Jun-2023</u> at <u>Ji</u>			ABS	Field Office: Shanghai, Ch	
Request Reviewed and NO	O Conflict of Interest Identif	ied.			
request reviewed and m	interest identifi			≫\	
	compliance with second			Runou of Chipping and is insued eatably for the use of the D	
DTE: This Certificate evidences committees, its clients or	other authorized entities. This	con the Rules, guides, standards, Certificate is a representation on	by that the Overla Lense space	Buleau of Shipping and is issued solely for the use of the Bureau of herein has been found to comply with one or more of the R fertificate is governed by the Rules and standards of American Bu	
	10 1 CA 1 D				