

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	Falcon Lease Pte 60 PAYA LEBAR	<u>Ltd</u> ROAD, #12-05, PAYA LEE	.409051 Owner No.: <u>FLNU 600859-1</u>		
Manufacturer & address	Jing Jiang Asian-F	Pacific Logistics Equipment	t Co., Ltd	Serial No.: <u>2210602</u>	
Manufacturer's Model Nº.: <u>A</u>					
APPLICABLE RULES, REC	GULATIONS AND STAND	ARDS			
ABS Design Type №: <u>AB/12</u>			US DOT Identification C	Code: <u>IA-8101</u>	
ABS Approval Ref. Nº: T2382295			US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>		
CSC Approval Reference: USA/AB-124/22			IMDG Approval Reference: USA/IMO/AB/124/22		
Customs Approval Reference: USA/124-AB/22			Sec. 6.7 ADR/RID Approval Number: NL/AB-124/22		
International Union of Railways (UIC): IRS 50592			Sec. 6.8 ADR/RID Approval Number: NL/AB-124/22		
Other(s): <u>TC, ISO 668, 1161</u>	1 <u>, 6346, 1496-3</u>		US DoT SP: <u>N/A</u> and/or	TC Equiv. Cert.: <u>N/A</u>	
CONTAINER CHARACTER	RISTICS				
SO Size/Type Code: 22K2					
Overall Length: <u>6058</u> mm		Wi	dth: <u>2438</u> mm	Height <u>2591</u> mm	
Maximum Operating Gross	Mass: <u>36000</u> kg	Т	are: <u>3760</u> kg	Max. Permissible Payload: 32240 kg	
Allowable Stacking Load for	1.8 g: <u>216000</u> kg		Transverse Racking Te	st Force: <u>150000</u> newtons	
ANK CHARACTERISTICS	6				
Design Code: ASME BPVC	VIII Div. 1 & EN 14025		Liquid Capacity at 20°C	: <u>25990</u> liters (total)	
Overall Tank Length: 6029 r	mm		Outside Tank Diameter:	: <u>2423</u> mm	
Head Matl Spec.: <u>SANS 500</u>	028-7:1.4402	Head Thickness: 4.6 m	nm (as built after forming)	Head Corrosion Allowance: 0.2 mm	
Shell Matl Spec.: SANS 500	28-7:1.4402	Shell Thickness: 4.6 m	m (as built)	Shell Corrosion Allowance: 0.42 mm	
Equiv. Reference Steel Thic	kness: <u>6</u> mm				
MAWP: <u>4.0</u> bar			MAWP of Heating Syste		
ixternal Design Pressure: 0.41 bar			Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C		
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm			Insulation: Type: Rockwool & Thickness: 50 mm		
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: <u>GRP</u> & Thickness: <u>1.8 / 2.0</u> mm Bottom Discharge No. of Closures in Series: <u>3</u>		
Discharge: <u>Bottom</u>			Bottom Discharge No. c	of Closures in Series: 3	
PRESSURE RELIEF DEVIC					
	1 st ; Quantity: <u>1</u>		2 nd ; Quantity: <u>N/A</u>	3 rd ; Quantity: <u>N/A</u>	
Manufacturer	GUARD				
Catalog Number	<u>AMF48001-00</u>		-	=	
Set Pressure	<u>4.4</u> bar		bar	<u></u> bar	
Rupture Capacity (each)	<u>N/A</u> bar <u>4.67</u> m³/s		<u></u> bar	<u></u> bar	
Total Capacity: <u>4.67</u> m ³ /s	<u>4.07</u> 1175		<u></u> m³/s	<u></u> m²/s	
SERVICE EQUIPMENT					
	Discharge Drevision 1 5	Airling			
Bottom Discharge, 3" Top	Discharge Provision, 1.5	Air line			
TESTING INFORMATION					
Prototype Test Certificate: S	<u>SQ5160313-A.R1</u> , dated: <u>2</u>	5-Mar-2022	Rail Impact Test Certific	cate/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>	
TC Impact Approved: <u>Yes</u>					
PRESSURE TEST					
Test Pressure of Tank: <u>6.0</u> bar, dated: <u>02-Jun-2023</u>		Test Pressure of Heating System: <u>6.0</u> bar, dated: <u>01-Jun-2023</u>			
_eak Proof Test of Containe					
Approved Commodities: Col		<u>s per T11 / L4BN</u>			
Portable Tank Instruction: T	<u>11</u>		ADR/RID Tank Code: L	<u>4BN</u>	
Marking: 02/06/2023 P B		CSC Plate Stamping Date: 06/2028 or ACEP Nº.: N/A			
Stamping ta	ink-plate		Next Inspection Date: 1	2/2025	
	-	between commodities and	service equipment/pressure	e relief devices/vessel/gaskets are the responsibility of th	
owner. Shipping name/spec	ial provisions markings are	the responsibility of the ov			
ssued on: <u>09-Jun-2023</u> at <u>J</u>	lingjiang,Jiangsu,China by	<u>Zhang, Mingjie (11395)</u>	(ADO)	Field Office: Shanghai, Chi	
Request Reviewed and N	O Conflict of Interest Identifi	ed.			
of Shipping who shall rer	es compliance with one or more r other authorized entities. This ler criteria of American Bureau or main the sole judge thereof. Not turer, seller, supplier, repairer, o	hing contained in this Certificat	te or in any Neodelissued in cor	Buleau of Shipping and is issued solely for the use of the Bureau ed hepein has been found to comply with one or more of the Ru eriflicate is governed by the Rules and standards of American Bur emplation of this Certificate shall be deemed to relieve any desig	