

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	Falcon Lease Pte			409051 Owner No.: FLNU 600861-0	
Vanufacturer		60 PAYA LEBAR ROAD. #12-05. PAYA LEBAR SQUARE.SINGAPORE.4090 Jing Jiang Asian-Pacific Logistics Equipment Co Ltd No. 199 Xingang Avenue, JingJiang City, Jiangsu Province, China			
& address				Serial No.: <u>2210604</u>	
Manufacturer's Model Nº.: <u>A</u>	023E-026-0002				
APPLICABLE RULES, REC	ULATIONS AND STAN	DARDS			
ABS Design Type №: <u>AB/12</u>	4/22		US DOT Identification Co	ode: <u>IA-8101</u>	
ABS Approval Ref. №: <u>T238</u>	2295		US DOT Approval: 49 CF	FR <u>§178.273, §178.274, §178.275</u>	
CSC Approval Reference: U	<u>SA/AB-124/22</u>		IMDG Approval Reference	ce: <u>USA/IMO/AB/124/22</u>	
Customs Approval Reference: USA/124-AB/22			Sec. 6.7 ADR/RID Approval Number: NL/AB-124/22		
International Union of Railways (UIC): IRS 50592			Sec. 6.8 ADR/RID Approval Number: NL/AB-124/22		
Other(s): <u>TC, ISO 668, 1161</u>	<u>, 6346, 1496-3</u>		US DoT SP: <u>N/A</u> and/or	TC Equiv. Cert.: <u>N/A</u>	
CONTAINER CHARACTER	ISTICS				
SO Size/Type Code: 22K2					
Overall Length: <u>6058</u> mm		Width	: <u>2438</u> mm	Height 2591 mm	
Maximum Operating Gross I	Mass: <u>36000</u> kg	Tare	e: <u>3760</u> kg	Max. Permissible Payload: 32240 kg	
Allowable Stacking Load for	1.8 g: <u>216000</u> kg		Transverse Racking Test	t Force: <u>150000</u> newtons	
TANK CHARACTERISTICS					
Design Code: ASME BPVC	VIII Div. 1 & EN 14025		Liquid Capacity at 20°C:	25890 liters (total)	
Overall Tank Length: 6029 r	nm		Outside Tank Diameter:	<u>2423</u> mm	
Head Matl Spec.: <u>SANS 500</u>	28-7:1.4402	Head Thickness: 4.6 mm		Head Corrosion Allowance: 0.2 mm	
Shell Matl Spec.: <u>SANS 500</u>	28-7:1.4402	Shell Thickness: 4.6 mm	as built)	Shell Corrosion Allowance: 0.42 mm	
Equiv. Reference Steel Thic	kness: <u>6</u> mm				
MAWP: <u>4.0</u> bar			MAWP of Heating Syster		
xternal Design Pressure: <u>0.41</u> bar			Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C		
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm			Insulation: Type: Rockwool & Thickness: 50 mm		
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: <u>GRP</u> & Thickness: <u>1.8 / 2.0</u> mm Bottom Discharge No. of Closures in Series: <u>3</u>		
Discharge: <u>Bottom</u>			Bottom Discharge No. of	Closures in Series: 3	
PRESSURE RELIEF DEVIC					
1	1 st ; Quantity: <u>1</u>		2 nd ; Quantity: <u>N/A</u>	3 rd ; Quantity: <u>N/A</u>	
Manufacturer	GUARD				
Catalog Number Set Pressure	<u>AMF48001-00</u>		= bar	<u></u>	
Rupture	<u>4.4</u> bar N/A bar		<u></u> bar <u></u> bar	bar bar	
Capacity (each)	<u>4.67</u> m ³ /s		<u></u> m ³ /s	<u> </u>	
Fotal Capacity: 4.67 m ³ /s	<u></u>				
3" Bottom Discharge, 3" Top	Discharge Provision 15	" Air line			
	Discharge Provision, 1.0				
Prototype Test Certificate: S	05160313-A R1_dated: 3	25-Mar-2022	Rail Impact Test Certific:	ate/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>	
FC Impact Approved: Yes	<u>Q3100313-A.R.</u> , ualed. <u>2</u>	<u>-0-Mai-2022</u>		alemepon. <u>0000000000777</u> , daled. <u>21-001-2022</u>	
PRESSURE TEST					
Test Pressure of Tank: 6.0 b	ar dated: 06- lun-2023		Test Pressure of Heating	System: 6.0 bar, dated: 03-Jun-2023	
Leak Proof Test of Containe	·	2023	rest riessure of rieating	3 System. <u>0.0</u> bar, dated. <u>05-5011-2025</u>	
Approved Commodities: Cor					
Portable Tank Instruction: <u>T</u>			ADR/RID Tank Code: <u>L4</u>	BN	
		2	ABRAND FURK COUR. <u>L4</u>		
Marking: 06/06	<u>5/2023 P</u> 🖞	3	CSC Plate Stamping Dat	te: <u>06/2028</u> or ACEP Nº.: <u>N/A</u>	
Stamping ta			Next Inspection Date: 12	/2025	
	-	between commodities and ser	vice equipment/pressure	relief devices/vessel/gaskets are the responsibility of the	
owner. Shipping name/spec	al provisions markings ar	e the responsibility of the owne			
ssued on: <u>09-Jun-2023</u> at <u>J</u>	ingjiang,Jiangsu,China by	Zhang, Mingjie (11395)	ABS	Field Office: <u>Shanghai, Chi</u>	
Request Reviewed and N	O Conflict of Interest Identif	ïed.			
		~			
TE: This Certificate evidence	s compliance with one or mor	e of the Rules, guides, standard, o	Mother Criterian American B	weau of Shipping and is issued solely for the use of the Bureau ad herein has been found to comply with one or more of the Ru entificate is governed by the Rules and standards of American Bur	