

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner Falcon Lease Pte Ltd & owner No.: FLNU 600864-7 & 60 PAYA LEBAR ROAD, #12-05, PAYA LEBAR SQUARE,SINGAPORE,409051

Manufacturer Jing Jiang Asian-Pacific Logistics Equipment Co., Ltd

& address No. 199 Xingang Avenue, JingJiang City, Jiangsu Province, China
Serial No.: 2210607

Manufacturer's Model Nº.: A023E-026-0002

APPLICABLE RULES, REGULATIONS AND STANDARDS

ABS Design Type №: AB/124/22 US DOT Identification Code: IA-8101

ABS Approval Ref. №: <u>T2382295</u>

US DOT Approval: 49 CFR <u>§178.273</u>, <u>§178.274</u>, <u>§178.275</u>,

CSC Approval Reference: <u>USA/IAB-124/22</u>
Customs Approval Reference: <u>USA/IAB-124/22</u>
Customs Approval Reference: <u>USA/124-AB/22</u>
International Union of Railways (UIC): <u>IRS 50592</u>
Other(s): <u>TC, ISO 668, 1161, 6346, 1496-3</u>

IMDG Approval Reference: <u>USA/IMO/AB/124/22</u>
Sec. 6.7 ADR/RID Approval Number: <u>NL/AB-124/22</u>
US DoT SP: <u>N/A</u> and/or TC Equiv. Cert.: <u>N/A</u>

CONTAINER CHARACTERISTICS

ISO Size/Type Code: 22K2

Overall Length: <u>6058</u> mm Width: <u>2438</u> mm Height <u>2591</u> mm

Maximum Operating Gross Mass: 36000 kg Tare: 3760 kg Max. Permissible Payload: 32240 kg

Allowable Stacking Load for 1.8 g: 216000 kg Transverse Racking Test Force: 150000 newtons

TANK CHARACTERISTICS

Design Code: ASME BPVC VIII Div. 1 & EN 14025 Liquid Capacity at 20°C: 26000 liters (total)

Overall Tank Length: 6029 mm Outside Tank Diameter: 2423 mm

Head Matl Spec.: SANS 50028-7:1.4402 Head Thickness: 4.6 mm (as built after forming) Head Corrosion Allowance: 0.2 mm
Shell Matl Spec.: SANS 50028-7:1.4402 Shell Thickness: 4.6 mm (as built) Shell Corrosion Allowance: 0.42 mm

Equiv. Reference Steel Thickness: 6 mm

MAWP: 4.0 bar MAWP of Heating System: 4.0 bar

External Design Pressure: <u>0.41</u> bar Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C

Coating/Lining: Type: N/A & Thickness: N/A mm

Insulation: Type: Rockwool & Thickness: 50 mm

Baffles: N/A Quantity: N/A

Cladding: Type: GRP & Thickness: 1.8 / 2.0 mm

Discharge: Bottom

Bottom Discharge No. of Closures in Series: 3

PRESSURE RELIEF DEVICES

1st; Quantity: <u>1</u> 2nd; Quantity: <u>N/A</u> 3rd; Quantity: <u>N/A</u>

 Manufacturer
 GUARD
 =
 =

 Catalog Number
 AMF48001-00
 =
 =

 Set Pressure
 4.4 bar
 =
 bar

 Rupture
 N/A bar
 =
 bar

 Capacity (each)
 4.67 m³/s
 =
 m³/s

Total Capacity: 4.67 m³/s

SERVICE EQUIPMENT

3" Bottom Discharge, 3" Top Discharge Provision, 1.5" Air line

TESTING INFORMATION

Prototype Test Certificate: SQ5160313-A.R1, dated: 25-Mar-2022 Rail Impact Test Certificate/Report: SQ5038404-A, dated: 21-Jan-2022

TC Impact Approved: Yes

PRESSURE TEST

Test Pressure of Tank: 6.0 bar, dated: 02-Jun-2023 Test Pressure of Heating System: 6.0 bar, dated: 01-Jun-2023

Leak Proof Test of Container: 1.0 bar, dated: 04-Jun-2023

Approved Commodities: Compatibilities commodities as per T11 / L4BN

Portable Tank Instruction: <u>T11</u> ADR/RID Tank Code: <u>L4BN</u>

Marking:

02/06/2023 P B CSC Plate Stamping Date: 06/2028 or ACEP Nº.: N/A

Stamping tank-plate Next Inspection Date: <u>12/2025</u>

Additional Information/Comments: The compatibilities between commodities and service equipment/pressure relief devices/vessel/gaskets are the responsibility of the

owner. Shipping name/special provisions markings are the responsibility of the owner.

Issued on: 09-Jun-2023 at Jingjiang, Jiangsu, China by Zhang, Mingjie (11395)

Request Reviewed and NO Conflict of Interest Identified.

TE: This Certificate evidences compliance with one or more of the Rules, guides, standard, or other entires. Am frictin Bureau of Shipping and is issued solely for the use of the Bureau, its committees, its clients or other authorized entities. This Certificate is a representation only that the control of the standards, or other criteria of American Bureau of Shipping. The validity, applicability and interpress of the criticate is governed by the Rules and standards of American Bureau of Shipping who shall remain the sole judge thereof. Nothing contained in this Certificate or in any Report issued in or templation of this Certificate shall be deemed to relieve any designer, builder, owner, manufacturer, seller, supplier, repairer, operator, or other entity of any warranty express of multical.

CNT-SFM-00058 Revision 4 Page 1 of 1

Field Office: Shanghai, China