

## American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	Falcon Lease Pte 60 PAYA LEBAR	<u>Ltd</u> ROAD, #12-05, PAYA LEBAI	9051 Owner No.: FLNU 600877-6		
Manufacturer & address	No. 199 Xingang	Pacific Logistics Equipment C Avenue, JingJiang City, Jiang	Serial No.: 2210620		
Manufacturer's Model №.: <u>A</u>	<u>4023E-026-0002</u>				
APPLICABLE RULES, REC	GULATIONS AND STAND	ARDS			
ABS Design Type №: <u>AB/12</u>	24/22		US DOT Identification C	Code: <u>IA-8101</u>	
ABS Approval Ref. Nº: T238	32295		US DOT Approval: 49 C	CFR <u>§178.273, §178.274, §178.275</u>	
CSC Approval Reference: USA/AB-124/22			IMDG Approval Reference: <u>USA/IMO/AB/124/22</u>		
Customs Approval Reference: USA/124-AB/22				roval Number: <u>NL/AB-124/22</u>	
International Union of Railways (UIC): IRS 50592			Sec. 6.8 ADR/RID Approval Number: <u>NL/AB-124/22</u> US DoT SP: <u>N/A</u> and/or TC Equiv. Cert.: <u>N/A</u>		
Other(s): <u>TC, ISO 668, 1161</u>			US DoT SP: <u>N/A</u> and/or	TC Equiv. Cert.: <u>N/A</u>	
CONTAINER CHARACTER	RISTICS				
SO Size/Type Code: 22K2					
Overall Length: <u>6058</u> mm			n: <u>2438</u> mm	Height <u>2591</u> mm	
Maximum Operating Gross		Tan	e: <u>3760</u> kg	Max. Permissible Payload: <u>32240</u> kg	
Allowable Stacking Load for			Transverse Racking Tes	st Force: <u>150000</u> newtons	
			11 110 11 10000		
Design Code: <u>ASME BPVC</u>			Liquid Capacity at 20°C:		
Overall Tank Length: 6029 r		Lload Thickness, 4.C mm	Outside Tank Diameter:		
Head Matl Spec.: <u>SANS 500</u>		Head Thickness: <u>4.6</u> mm		Head Corrosion Allowance: 0.2 mm	
Shell Matl Spec.: <u>SANS 500</u> Equiv. Reference Steel Thic		Shell Thickness: 4.6 mm	(as Dulit)	Shell Corrosion Allowance: 0.42 mm	
	kness: <u>o</u> mm		MAWP of Hoating Syste	am: 4.0 har	
WP: <u>4.0</u> bar ternal Design Pressure: <u>0.41</u> bar		P 1	MAWP of Heating System: <u>4.0</u> bar Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C		
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm			Insulation: Type: <u>Rockwool</u> & Thickness: <u>50</u> mm		
Baffles: $N/A$ Quantity: $N/A$			Cladding: Type: <u>GRP</u> & Thickness: <u>1.8 / 2.0</u> mm		
Discharge: <u>Bottom</u>			Bottom Discharge No. o		
PRESSURE RELIEF DEVIC	CES				
	1 <sup>st</sup> ; Quantity: <u>1</u>		2 <sup>nd</sup> ; Quantity: N/A	3 <sup>rd</sup> ; Quantity: <u>N/A</u>	
Manufacturer	GUARD				
Catalog Number	AMF48001-00				
Set Pressure	<u>4.4</u> bar		<u></u> bar	<u></u> bar	
Rupture	<u>N/A</u> bar		<u></u> bar	<u></u> bar	
Capacity (each)	<u>4.67</u> m <sup>3</sup> /s		<u></u> m <sup>3</sup> /s	<u></u> m³/s	
Total Capacity: <u>4.67</u> m <sup>3</sup> /s					
SERVICE EQUIPMENT					
3" Bottom Discharge, 3" Top	p Discharge Provision, 1.5	Air line			
<b>TESTING INFORMATION</b>					
Prototype Test Certificate: S	SQ5160313-A.R1, dated: 2	5-Mar-2022	Rail Impact Test Certific	cate/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>	
TC Impact Approved: <u>Yes</u>					
PRESSURE TEST					
Test Pressure of Tank: 6.0 t	bar, dated: <u>03-Jun-2023</u>		Test Pressure of Heating	g System: <u>6.0</u> bar, dated: <u>02-Jun-2023</u>	
_eak Proof Test of Containe	er: <u>1.0</u> bar, dated: <u>05-Jun-2</u>	023			
Approved Commodities: Co	mpatibilities commodities a	s per T11 / L4BN			
Portable Tank Instruction: T	<u>11</u>		ADR/RID Tank Code: L4	<u>4BN</u>	
03/06	6/2023 P Æ	}	CSC Plate Stamping Da	ate: <u>06/2028</u> or ACEP №.: <u>N/A</u>	
-			Next Inspection Date: 12	2/2025	
Stamping ta	-				
		between commodities and se the responsibility of the own		e relief devices/vessel/gaskets are the responsibility of th	
Issued on: <u>09-Jun-2023</u> at J			ABS	Field Office: Shanghai, Chi	
Request Reviewed and <u>N</u>	O Conflict of Interest Identifi	ed.			
DTE: This Certificate evidence committees, its clients o guides, standards, or oth of Shipping who shall re builder, owner, manufact	es compliance with one or more r other authorized entities. This ler criteria of American Bureau main the sole judge thereof. No turer, seller, supplier, repairer, o	of the Rules, guides, standard Certificate is a represention on of Shipping. The validity, applicabil thing contained in this Certificate o operator, or other entity of any war	O offeneries of American ly that the Astronomy and the Astronomy ity and interpret action and or in any Nepton sected in part ranty express of multican	Bureau of Shipping and is issued solely for the use of the Bureau and the pein has been found to comply with one or more of the Ru Artificate is governed by the Rules and standards of American Bur templation of this Certificate shall be deemed to relieve any desig	