

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	Falcon Lease Pte 60 PAYA LEBAR F	<u>_td</u> ROAD, #12-05, PAYA LEBA	AR SQUARE, SINGAPORE	E.409051 Owner No.: FLNU 600878-1	
Manufacturer & address	Jing Jiang Asian-P	acific Logistics Equipment (venue, JingJiang City, Jian	Co., Ltd	Serial No.: <u>2210621</u>	
Manufacturer's Model Nº.: <u>A</u>					
APPLICABLE RULES, REG	GULATIONS AND STAND	ARDS			
ABS Design Type №: <u>AB/12</u>			US DOT Identification C	Code: <u>IA-8101</u>	
ABS Approval Ref. №: <u>T2382295</u>			US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>		
CSC Approval Reference: USA/AB-124/22			IMDG Approval Reference: USA/IMO/AB/124/22		
Customs Approval Reference: USA/124-AB/22			Sec. 6.7 ADR/RID Approval Number: NL/AB-124/22		
International Union of Railways (UIC): <u>IRS 50592</u>			Sec. 6.8 ADR/RID Approval Number: NL/AB-124/22		
Other(s): <u>TC, ISO 668, 1161</u>	<u>, 6346, 1496-3</u>		US DoT SP: <u>N/A</u> and/or	TC Equiv. Cert.: <u>N/A</u>	
CONTAINER CHARACTER	ISTICS				
SO Size/Type Code: 22K2					
Overall Length: <u>6058</u> mm		Wid	th: <u>2438</u> mm	Height <u>2591</u> mm	
Maximum Operating Gross	Mass: <u>36000</u> kg	Та	re: <u>3760</u> kg	Max. Permissible Payload: 32240 kg	
Allowable Stacking Load for	1.8 g: <u>216000</u> kg		Transverse Racking Te	st Force: 150000 newtons	
ANK CHARACTERISTICS	6				
Design Code: ASME BPVC	VIII Div. 1 & EN 14025		Liquid Capacity at 20°C	: 25940 liters (total)	
Overall Tank Length: 6029 r			Outside Tank Diameter:	: <u>2423</u> mm	
lead Matl Spec.: SANS 500		Head Thickness: 4.6 mm	n (as built after forming)	Head Corrosion Allowance: 0.2 mm	
Shell Matl Spec.: <u>SANS 500</u>		Shell Thickness: 4.6 mm	n (as built)	Shell Corrosion Allowance: 0.42 mm	
Equiv. Reference Steel Thic	kness: <u>6</u> mm				
MAWP: <u>4.0</u> bar			MAWP of Heating Syste		
xternal Design Pressure: <u>0.41</u> bar			Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C		
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm			Insulation: Type: <u>Rockwool</u> & Thickness: <u>50</u> mm		
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: <u>GRP</u> & Thickness: <u>1.8 / 2.0</u> mm Bottom Discharge No. of Closures in Series: <u>3</u>		
Discharge: <u>Bottom</u>			Bottom Discharge No. c	or Closures in Series: 3	
PRESSURE RELIEF DEVIC					
lanufacturar	1 st ; Quantity: <u>1</u>		2 nd ; Quantity: <u>N/A</u>	3 rd ; Quantity: <u>N/A</u>	
Manufacturer	GUARD				
Catalog Number Set Pressure	<u>AMF48001-00</u>		=		
Rupture	<u>4.4</u> bar <u>N/A</u> bar		<u></u> bar <u></u> bar	bar bar	
Capacity (each)	4.67 m ³ /s		<u></u> m ³ /s	<u> </u>	
Fotal Capacity: <u>4.67</u> m ³ /s	<u></u> ,o				
SERVICE EQUIPMENT					
3" Bottom Discharge, 3" Top	Discharge Provision 15"	Air line			
	Discharge i Tovision, 1.5				
Prototype Test Certificate: S	OE160212 A B1 datad: 25	Mor 2022	Roil Impost Tost Cortific	cate/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>	
Folotype Test Certificate. <u>S</u> FC Impact Approved: <u>Yes</u>	<u>5Q5160313-A.R.I</u> , daled. <u>25</u>	<u>Mai-2022</u>	Rail Impact Test Certific	ale/Report: <u>SQ5036404-A</u> , daled: <u>21-Jan-2022</u>	
PRESSURE TEST					
			Test Dessey of Heatin	- Outbarry C.O.h.e., data di O.O. hun 2000	
est Pressure of Tank: <u>6.0</u> bar, dated: <u>03-Jun-2023</u> .eak Proof Test of Container: <u>1.0</u> bar, dated: <u>05-Jun-2023</u>		Test Pressure of Heating System: <u>6.0</u> bar, dated: <u>02-Jun-2023</u>			
Approved Commodities: <u>Co</u>		<u>s per 111 / L4Bin</u>	ADD/DID Tank Cadau I	400	
Portable Tank Instruction: T	<u></u>		ADR/RID Tank Code: L	<u>4DIN</u>	
Marking: 03/06/2023 P B		CSC Plate Stamping Da	ate: <u>06/2028</u> or ACEP №.: <u>N/A</u>		
Stamping ta	nk-plate		Next Inspection Date: 1	2/2025	
				e relief devices/vessel/gaskets are the responsibility of th	
owner. Shipping name/spec ssued on: 09-Jun-2023 at J			ner.	Field Office: Shanghai, Chi	
<u> </u>				Field Office: Snanghal, Chi	
Request Reviewed and N	O Conflict of Interest Identifie	:d		► \	
DTE: This Certificate evidence committees, its clients o guides, standards, or oth of Shipping who shall rer	es compliance with one or more r other authorized entities. This er criteria of American Bureau o main the sole judge thereof. Not urer, seller, supplier, repairer, o	of the Rules, guides, standard Certificate is a representation o f Shipping. The validity, applicab ning contained in this Certificate	Cotteneries American nly that the Oot ceres save ility and interprete source and or in any beautissue on cere	Buleau of Shipping and is issued solely for the use of the Bureau ed herein has been found to comply with one or more of the Ru ertificate is governed by the Rules and standards of American Bur templation of this Certificate shall be deemed to relieve any desig	