

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	<u>Falcon Lease Pte</u> <u>60 PAYA LEBAR</u>	<u>Ltd</u> ROAD, #12-05, PAYA LEBA	<u>R SQUARE.SIN</u> GAPORE	.409051 Owner No.: FLNU 600881-6	
Manufacturer & address	Jing Jiang Asian-I	Pacific Logistics Equipment C Avenue, JingJiang City, Jiang	Serial No.: <u>2210624</u>		
Manufacturer's Model Nº.: <u>A</u>		wende, ungolang eity, uan			
		APDS			
APPLICABLE RULES, REG ABS Design Type Nº: AB/12		ARDS	US DOT Identification C	odo: 14 8101	
ABS Approval Ref. №: T238				FR <u>§178.273, §178.274, §178.275</u>	
CSC Approval Reference: USA/AB-124/22				ce: <u>USA/IMO/AB/124/22</u>	
Customs Approval Reference: USA/124-AB/22			Sec. 6.7 ADR/RID Approval Number: <u>NL/AB-124/22</u>		
International Union of Railways (UIC): IRS 50592			Sec. 6.8 ADR/RID Approval Number: NL/AB-124/22		
Other(s): TC, ISO 668, 1161, 6346, 1496-3			US DoT SP: <u>N/A</u> and/or TC Equiv. Cert.: <u>N/A</u>		
CONTAINER CHARACTER	ISTICS				
SO Size/Type Code: 22K2					
Overall Length: 6058 mm		Widt	h: <u>2438</u> mm	Height 2591 mm	
Maximum Operating Gross	Mass: <u>36000</u> kg	Tar	e: <u>3760</u> kg	Max. Permissible Payload: 32240 kg	
Allowable Stacking Load for	1.8 g: <u>216000</u> kg		Transverse Racking Tes	st Force: 150000 newtons	
TANK CHARACTERISTICS					
Design Code: ASME BPVC	VIII Div. 1 & EN 14025		Liquid Capacity at 20°C:	25960 liters (total)	
Overall Tank Length: <u>6029</u> n	nm		Outside Tank Diameter:	<u>2423</u> mm	
Head Matl Spec.: <u>SANS 500</u>	28-7:1.4402	Head Thickness: 4.6 mm	(as built after forming)	Head Corrosion Allowance: 0.2 mm	
Shell Matl Spec.: <u>SANS 500</u>	28-7:1.4402	Shell Thickness: 4.6 mm	(as built)	Shell Corrosion Allowance: 0.42 mm	
Equiv. Reference Steel Thick	kness: <u>6</u> mm				
MAWP: <u>4.0</u> bar			MAWP of Heating Syste	m: <u>4.0</u> bar	
External Design Pressure: 0	ernal Design Pressure: 0.41 bar		Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C		
coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm			Insulation: Type: Rockwool & Thickness: 50 mm		
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: GRP & Thickness: <u>1.8 / 2.0</u> mm		
Discharge: Bottom			Bottom Discharge No. or	f Closures in Series: <u>3</u>	
PRESSURE RELIEF DEVIC	ES				
	1 st ; Quantity: <u>1</u>		2 nd ; Quantity: <u>N/A</u>	3 rd ; Quantity: <u>N/A</u>	
Manufacturer	GUARD				
Catalog Number	AMF48001-00		=	=	
Set Pressure	<u>4.4</u> bar		<u></u> bar	<u></u> bar	
Rupture	<u>N/A</u> bar		<u></u> bar	<u></u> bar	
Capacity (each)	<u>4.67</u> m ³ /s		<u></u> m³/s	<u></u> m³/s	
Total Capacity: <u>4.67</u> m ³ /s					
SERVICE EQUIPMENT					
3" Bottom Discharge, 3" Top	Discharge Provision, 1.5	' Air line			
TESTING INFORMATION					
Prototype Test Certificate: <u>S</u> TC Impact Approved: <u>Yes</u>	<u>Q5160313-A.R1</u> , dated: <u>2</u>	<u>5-Mar-2022</u>	Rail Impact Test Certific	ate/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>	
PRESSURE TEST					
Test Pressure of Tank: 6.0 b	oar, dated: <u>02-Jun-2023</u>		Test Pressure of Heating	g System: <u>6.0</u> bar, dated: <u>02-Jun-2023</u>	
eak Proof Test of Containe	r: <u>1.0</u> bar, dated: <u>03-Jun-2</u>	023			
Approved Commodities: Cor	npatibilities commodities a	as per T11 / L4BN			
Portable Tank Instruction: T	11		ADR/RID Tank Code: L4	<u>IBN</u>	
Marking: 02/06	6/2023 P Æ	}	CSC Plate Stamping Da	te: <u>06/2028</u> or ACEP Nº.: <u>N/A</u>	
Marking: <u>02700</u> Stamping ta			Next Inspection Date: 12	2/2025	
	-	hetween commodities and se	vice equipment/pressure	relief devices/vessel/gaskets are the responsibility of the	
owner. Shipping name/speci	al provisions markings are	e the responsibility of the owr			
Issued on: <u>09-Jun-2023</u> at <u>Ji</u>	ingjiang,Jiangsu,China by	Zhang, Mingjie (11395)	ABS	Field Office: <u>Shanghai, Chi</u>	
Request Reviewed and No.	O Conflict of Interest Identif	ied.			
OTE: This Certificate evidence committees, its clients or guides, standards, or oth	s compliance with one or more other authorized entities. This er criteria of American Bureau pain the sole indre thereof. No	e of the Rules, guides, standard certificate is a representation or of Shipping. The validity, applicability	O of encrite and American E ly that the orthogen areas lity and interpretation units of	Sureau of Shipping and is issued solely for the use of the Bureau of hepein has been found to comply with one or more of the Ru ertificate is governed by the Rules and standards of American Bu remplation of this Certificate shall be deemed to relieve any desig	