

## American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	<u>Falcon Lease Pte</u> 60 PAYA LEBAR	<u>Ltd</u> ROAD, #12-05, PAYA LEB	.409051 Owner No.: FLNU 600888-4		
Manufacturer & address	Jing Jiang Asian-P	Pacific Logistics Equipment Avenue, JingJiang City, Jia	Co., Ltd	Serial No.: <u>2210631</u>	
Manufacturer's Model Nº.: <u>A</u>					
APPLICABLE RULES, REC	ULATIONS AND STAND	ARDS			
ABS Design Type №: <u>AB/12</u>			US DOT Identification C	Code: <u>IA-8101</u>	
ABS Approval Ref. №: <u>T2382295</u>			US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>		
CSC Approval Reference: USA/AB-124/22			IMDG Approval Reference: USA/IMO/AB/124/22		
Customs Approval Reference: USA/124-AB/22			Sec. 6.7 ADR/RID Approval Number: <u>NL/AB-124/22</u>		
International Union of Railways (UIC): IRS 50592			Sec. 6.8 ADR/RID Approval Number: NL/AB-124/22		
Other(s): <u>TC, ISO 668, 1161</u>	<u>, 6346, 1496-3</u>		US DoT SP: <u>N/A</u> and/or	r TC Equiv. Cert.: <u>N/A</u>	
CONTAINER CHARACTER	ISTICS				
SO Size/Type Code: 22K2					
Overall Length: <u>6058</u> mm		Wie	dth: <u>2438</u> mm	Height <u>2591</u> mm	
Maximum Operating Gross	Mass: <u>36000</u> kg	Ta	are: <u>3760</u> kg	Max. Permissible Payload: 32240 kg	
Allowable Stacking Load for	1.8 g: <u>216000</u> kg		Transverse Racking Te	st Force: 150000 newtons	
ANK CHARACTERISTICS	6				
Design Code: ASME BPVC	VIII Div. 1 & EN 14025		Liquid Capacity at 20°C	: <u>25960</u> liters (total)	
Overall Tank Length: 6029 r	nm		Outside Tank Diameter:	: <u>2423</u> mm	
lead Matl Spec.: SANS 500	028-7:1.4402	Head Thickness: 4.6 m	m (as built after forming)	Head Corrosion Allowance: 0.2 mm	
Shell Matl Spec.: SANS 500	28-7:1.4402	Shell Thickness: 4.6 mi	m (as built)	Shell Corrosion Allowance: 0.42 mm	
Equiv. Reference Steel Thic	kness: <u>6</u> mm				
MAWP: <u>4.0</u> bar			MAWP of Heating Syste		
External Design Pressure: <u>0.41</u> bar			Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C		
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm			Insulation: Type: <u>Rockwool</u> & Thickness: <u>50</u> mm		
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: <u>GRP</u> & Thickness: <u>1.8 / 2.0</u> mm Bottom Discharge No. of Closures in Series: <u>3</u>		
Discharge: <u>Bottom</u>			Bottom Discharge No. c	of Closures in Series: 3	
PRESSURE RELIEF DEVIC					
	1 <sup>st</sup> ; Quantity: <u>1</u>		2 <sup>nd</sup> ; Quantity: <u>N/A</u>	3 <sup>rd</sup> ; Quantity: <u>N/A</u>	
Manufacturer	<u>GUARD</u>				
Catalog Number	<u>AMF48001-00</u>		=	=	
Set Pressure	<u>4.4</u> bar		bar	<u></u> bar	
Rupture Capacity (each)	<u>N/A</u> bar <u>4.67</u> m³/s		<u></u> bar	<u></u> bar	
Total Capacity: <u>4.67</u> m <sup>3</sup> /s	<u>4.07</u> 1175		<u></u> m³/s	<u></u> m³/s	
SERVICE EQUIPMENT					
	Discharge Dravision 1 E	Airline			
B" Bottom Discharge, 3" Top	Discharge Provision, 1.5	Air line			
TESTING INFORMATION					
Prototype Test Certificate: <u>S</u>	<u>Q5160313-A.R1</u> , dated: <u>2</u>	<u>5-Mar-2022</u>	Rail Impact Test Certific	cate/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>	
TC Impact Approved: <u>Yes</u>					
PRESSURE TEST					
Test Pressure of Tank: <u>6.0</u> bar, dated: <u>03-Jun-2023</u>		Test Pressure of Heating System: <u>6.0</u> bar, dated: <u>02-Jun-2023</u>			
Leak Proof Test of Containe	r: <u>1.0</u> bar, dated: <u>04-Jun-2</u>	023			
Approved Commodities: Con	mpatibilities commodities a	as per T11 / L4BN			
Portable Tank Instruction: <u>T</u>	<u>11</u>		ADR/RID Tank Code: L	<u>4BN</u>	
Marking: 03/06/2023 P B		CSC Plate Stamping Date: 06/2028 or ACEP Nº.: N/A			
Stamping ta			Next Inspection Date: 1	2/2025	
	-	between commodities and	service equipment/pressure	e relief devices/vessel/gaskets are the responsibility of th	
wner. Shipping name/spec	ial provisions markings are	e the responsibility of the ov			
ssued on: <u>09-Jun-2023</u> at <u>J</u>	ingjiang,Jiangsu,China by	<u>Zhang, Mingjie (11395)</u>	ADO	Field Office: Shanghai, Chi	
Request Reviewed and N	O Conflict of Interest Identifi	ied.			
of Shipping who shall rer	s compliance with one or more other authorized entities. This er criteria of American Bureau nain the sole judge thereof. No urer, seller, supplier, repairer,	thing contained in this Certificati	e or in any Nebolassued in cor	Buleau of Shipping and is issued solely for the use of the Bureau bed herein has been found to comply with one or more of the Ru eritificate is governed by the Rules and standards of American Bur templation of this Certificate shall be deemed to relieve any desig	