

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	Falcon Lease Pte		Owner No.: FLNU 600890-3		
Manufacturer		60 PAYA LEBAR ROAD, #12-05, PAYA LEBAR SQUARE,SING/ Jing Jiang Asian-Pacific Logistics Equipment Co., Ltd		<u>PORE,409051</u>	
address		Avenue, JingJiang City, Jiang	Serial No.: 2210633		
Manufacturer's Model №.:	A023E-026-0002				
APPLICABLE RULES, RE	GULATIONS AND STAND	ARDS			
ABS Design Type №: <u>AB/1</u>	24/22		US DOT Identification (Code: <u>IA-8101</u>	
ABS Approval Ref. Nº: T2382295			US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>		
CSC Approval Reference: USA/AB-124/22			IMDG Approval Reference: USA/IMO/AB/124/22		
Customs Approval Reference: USA/124-AB/22			Sec. 6.7 ADR/RID Approval Number: NL/AB-124/22		
International Union of Railways (UIC): IRS 50592			Sec. 6.8 ADR/RID Approval Number: <u>NL/AB-124/22</u> US DoT SP: <u>N/A</u> and/or TC Equiv. Cert.: <u>N/A</u>		
other(s): <u>TC, ISO 668, 116</u>			US DoT SP: <u>N/A</u> and/or	TC Equiv. Cert.: <u>N/A</u>	
ONTAINER CHARACTE					
SO Size/Type Code: 22K2					
Overall Length: <u>6058</u> mm	Maran 00000 hrs		h: <u>2438</u> mm	Height <u>2591</u> mm	
Iaximum Operating Gross Ilowable Stacking Load fo		Tai	e: <u>3760</u> kg Transverse Backing Te	Max. Permissible Payload: <u>32240</u> kg st Force: 150000 newtons	
			Transverse Racking Te	at role. <u>130000</u> newtons	
esign Code: ASME BPVC		Concession of the local division of the loca	Liquid Capacity at 20°C	· 25930 liters (total)	
Verall Tank Length: 6029			Outside Tank Diameter		
lead Matl Spec.: <u>SANS 50</u>		Head Thickness: <u>4.6</u> mm		Head Corrosion Allowance: 0.2 mm	
hell Matl Spec.: SANS 50		Shell Thickness: 4.6 mm		Shell Corrosion Allowance: 0.42 mm	
quiv. Reference Steel Thi			· · · ·		
MAWP: <u>4.0</u> bar			MAWP of Heating Syste	em: <u>4.0</u> bar	
External Design Pressure: 0.41 bar			Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C		
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm			Insulation: Type: Rockwool & Thickness: 50 mm		
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: <u>GRP</u> & Thickness: <u>1.8 / 2.0</u> mm		
Discharge: Bottom			Bottom Discharge No. o	of Closures in Series: <u>3</u>	
PRESSURE RELIEF DEVI					
	1 st ; Quantity: <u>1</u>		2 nd ; Quantity: <u>N/A</u>	3 rd ; Quantity: <u>N/A</u>	
Manufacturer	GUARD				
Catalog Number Set Pressure	<u>AMF48001-00</u> <u>4.4</u> bar		bar	bar	
Rupture	<u>N/A</u> bar		<u></u> bar	- bar	
Capacity (each)	4.67 m ³ /s		<u></u> m ³ /s	<u> </u>	
Fotal Capacity: <u>4.67</u> m ³ /s				The second secon	
SERVICE EQUIPMENT					
"Bottom Discharge, 3" To	p Discharge Provision, 1.5	' Air line			
ESTING INFORMATION					
Prototype Test Certificate:	<u>SQ5160313-A.R1, dated: 2</u>	5-Mar-2022	Rail Impact Test Certific	cate/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>	
C Impact Approved: Yes					
PRESSURE TEST					
Test Pressure of Tank: 6.0 bar, dated: 03-Jun-2023			Test Pressure of Heating System: 6.0 bar, dated: 02-Jun-2023		
eak Proof Test of Contain	er: <u>1.0</u> bar, dated: <u>05-Jun-2</u>	023			
Approved Commodities: Co	ompatibilities commodities	as per T11 / L4BN			
Portable Tank Instruction:	<u>[11</u>		ADR/RID Tank Code: L	4BN	
)	CSC Plate Stamping D	ate: <u>06/2028</u> or ACEP №.: <u>N/A</u>	
Marking: 03/0	<u>6/2023 P</u> /±)		<u></u>	
Stamping t			Next Inspection Date: 1	2/2025	
dditional Information/Com	ments: The compatibilities			e relief devices/vessel/gaskets are the responsibility of th	
		the responsibility of the own	er.	Eicld Office: Characteric Offi	
	<u>Jingjiang,Jiangsu,China</u> by			Field Office: <u>Shanghai, Chi</u>	
Request Reviewed and <u>N</u>	NO Conflict of Interest Identif	ed.		► \	
		~			
DTE: This Certificate evidence	es compliance with one or mor	e of the Rules, guides, standard	Orothen criterine American	Buleau of Shipping and is issued solely for the use of the Bureau and the second sole of the Bureau sole of the Bureau certificate is governed by the Rules and standards of American Bur managing of this Certificate shall be deemed to reliave any design	
CONTRACT CONTRACTOR CONTRACT	or other authorized entities. This	centinuate is a representation of		ped negen has been round to comply with one or more of the RU	