

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	<u>Falcon Lease Pte</u> 60 PAYA LEBAR	<u>Ltd</u> ROAD, #12-05, PAYA LEBAI	R SQUARE.SINGAPORF	409051	Owner No.: FLNU 600892-4	
Manufacturer & address	Jing Jiang Asian-I	Pacific Logistics Equipment C Avenue, JingJiang City, Jiang	o., Ltd		Serial No.: <u>2210635</u>	
Manufacturer's Model Nº.:		wende, ungolang eity, uang				
		ADDS				
ABS Design Type Nº: <u>AB/1</u>	EGULATIONS AND STAND	ARDS	LIS DOT Identification C			
ABS Design Type Nº. <u>AB/124/22</u> ABS Approval Ref. Nº: <u>T2382295</u>			US DOT Identification Code: <u>IA-8101</u> US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>			
CSC Approval Reference: USA/AB-124/22			IMDG Approval Reference: USA/IMO/AB/124/22			
Customs Approval Reference: USA/124-AB/22			Sec. 6.7 ADR/RID Appro			
International Union of Railways (UIC): IRS 50592			Sec. 6.8 ADR/RID Appro			
Other(s): <u>TC, ISO 668, 116</u>			US DoT SP: <u>N/A</u> and/or TC Equiv. Cert.: <u>N/A</u>			
CONTAINER CHARACTE	RISTICS					
SO Size/Type Code: 22K2	2					
Overall Length: 6058 mm		Width	n: <u>2438</u> mm	Height 259	<u>1</u> mm	
Maximum Operating Gross	s Mass: <u>36000</u> kg	Tar	e: <u>3760</u> kg	Max. Perm	issible Payload: <u>32240</u> kg	
Allowable Stacking Load for	or 1.8 g: <u>216000</u> kg		Transverse Racking Tes	t Force: <u>150000</u> new	tons	
ANK CHARACTERISTIC	s					
Design Code: ASME BPV	C VIII Div. <u>1 & EN</u> 14025		Liquid Capacity at 20°C:	25930 liters (total)		
Overall Tank Length: 6029			Outside Tank Diameter:			
lead Matl Spec.: SANS 50		Head Thickness: 4.6 mm	(as built after forming)	Head Corro	sion Allowance: 0.2 mm	
Shell Matl Spec.: SANS 50	0028-7:1.4402	Shell Thickness: 4.6 mm	(as built)	Shell Corros	sion Allowance: 0.42 mm	
Equiv. Reference Steel Th	ickness: <u>6</u> mm					
MAWP: <u>4.0</u> bar			MAWP of Heating System	m: <u>4.0</u> bar		
xternal Design Pressure: 0.41 bar			Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C			
Coating/Lining: Type: <u>N/A</u>	& Thickness: <u>N/A</u> mm		Insulation: Type: Rockwool & Thickness: 50 mm			
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: GRP & Thickness: 1.8 / 2.0 mm			
Discharge: Bottom			Bottom Discharge No. of	Closures in Series:	<u>3</u>	
PRESSURE RELIEF DEV	ICES					
	1 st ; Quantity: <u>1</u>		2 nd ; Quantity: <u>N/A</u>		3 rd ; Quantity: <u>N/A</u>	
Manufacturer	GUARD				=	
Catalog Number	<u>AMF48001-00</u>		-		-	
Set Pressure	<u>4.4</u> bar		<u></u> bar		<u></u> bar	
Rupture	<u>N/A</u> bar		<u></u> bar		bar	
Capacity (each)	<u>4.67</u> m ³ /s		<u></u> m³/s		<u></u> m³/s	
Fotal Capacity: <u>4.67</u> m ³ /s						
SERVICE EQUIPMENT						
3" Bottom Discharge, 3" To	op Discharge Provision, 1.5	<u>' Air line</u>				
TESTING INFORMATION						
Prototype Test Certificate:	SQ5160313-A.R1, dated: 2	<u>5-Mar-2022</u>	Rail Impact Test Certifica	ate/Report: <u>SQ50384</u>	04-A, dated: 21-Jan-2022	
TC Impact Approved: Yes						
PRESSURE TEST						
Fest Pressure of Tank: 6.0) bar, dated: <u>03-Jun-2023</u>		Test Pressure of Heating	y System: <u>6.0</u> bar, da	ted: <u>02-Jun-2023</u>	
eak Proof Test of Contair	ner: <u>1.0</u> bar, dated: <u>05-Jun-2</u>	023				
Approved Commodities: <u>C</u>	ompatibilities commodities a	as per T11 / L4BN				
Portable Tank Instruction:	<u>T11</u>		ADR/RID Tank Code: L4	BN		
03/0	6/2023 P	3	CSC Plate Stamping Dat	te: 06/2028 or ACEP	№.: <u>N/A</u>	
Marking: 00/0			Next Inspection Date: 42	2/2025		
Stamping	-		Next Inspection Date: <u>12</u>			
		between commodities and se the responsibility of the own		relief devices/vessel	/gaskets are the responsibility of th	
	<u>Jingjiang, Jiangsu, China</u> by		ABS		Field Office: Shanghai, Chi	
	NO Conflict of Interest Identif		AR			
of Shipping who shall re	emain the sole judge thereof. No	e of the Rules, guides, standard certificate is a represervition on of Shipping. The validity, applicabil thing contained in this Certificate o operator, or other entity of any war	or in any Nebourissued in cert	uyeau of Shipping and is ed herein has been fou rrifficate is governed by t emplation of this Certific	s issued solely for the use of the Bureau nd to comply with one or more of the Ru he Rules and standards of American Bur ate shall be deemed to relieve any design	