

American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	Falcon Lease Pte 60 PAYA LEBAR	<u>Ltd</u> ROAD, #12-05, PAYA LE	E.409051 Owner No.: FLNU 600898-7		
Manufacturer & address	Jing Jiang Asian-F	Pacific Logistics Equipment	nt Co., Ltd	Serial No : 2210641	
Manufacturer's Model Nº.: <u>/</u>				<u></u>	
	CUL ATIONS AND STAND	APDS			
ABS Design Type №: <u>AB/1</u>	GULATIONS AND STAND	ARDS	US DOT Identification C	Codo: 10. 8101	
ABS Design Type Nº. <u>AB/124/22</u> ABS Approval Ref. Nº: <u>T2382295</u>			US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>		
CSC Approval Reference: USA/AB-124/22			IMDG Approval Reference: <u>USA/IMO/AB/124/22</u>		
Customs Approval Reference: USA/124-AB/22				roval Number: NL/AB-124/22	
International Union of Railways (UIC): IRS 50592				oval Number: <u>NL/AB-124/22</u>	
Other(s): TC, ISO 668, 1161, 6346, 1496-3			US DoT SP: <u>N/A</u> and/or TC Equiv. Cert.: <u>N/A</u>		
SO Size/Type Code: <u>22K2</u>					
Overall Length: <u>6058</u> mm		V	Vidth: <u>2438</u> mm	Height <u>2591</u> mm	
Maximum Operating Gross	Mass: 36000 kg		Tare: <u>3760</u> kg	Max. Permissible Payload: <u>32240</u> kg	
Allowable Stacking Load fo				st Force: 150000 newtons	
Design Code: ASME BPVC			Liquid Capacity at 20°C	: 25960 liters (total)	
Overall Tank Length: 6029			Outside Tank Diameter:		
lead Matl Spec.: SANS 50		Head Thickness: 4.6	mm (as built after forming)	Head Corrosion Allowance: 0.2 mm	
Shell Matl Spec.: SANS 500		Shell Thickness: 4.6 r		Shell Corrosion Allowance: 0.42 mm	
Equiv. Reference Steel Thi					
MAWP: <u>4.0</u> bar	_		MAWP of Heating Syste	em: 4.0 bar	
External Design Pressure: <u>0.41</u> bar			Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C		
Coating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm		- 1A	Insulation: Type: <u>Rockwool</u> & Thickness: <u>50</u> mm		
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: <u>GRP</u> & Thickness: <u>1.8 / 2.0</u> mm		
Discharge: Bottom			Bottom Discharge No. c	of Closures in Series: <u>3</u>	
PRESSURE RELIEF DEVI	CES		1		
	1 st ; Quantity: <u>1</u>		2 nd ; Quantity: <u>N/A</u>	3 rd ; Quantity: <u>N/A</u>	
Vanufacturer	GUARD				
Catalog Number	AMF48001-00			=	
Set Pressure	<u>4.4</u> bar		<u></u> bar	<u></u> bar	
Rupture	<u>N/A</u> bar		<u></u> bar	<u></u> bar	
Capacity (each)	<u>4.67</u> m ³ /s		<u></u> m³/s	<u></u> m³/s	
Total Capacity: <u>4.67</u> m³/s					
SERVICE EQUIPMENT					
3" Bottom Discharge, 3" To	p Discharge Provision, 1.5"	Air line			
TESTING INFORMATION					
Prototype Test Certificate:	<u>SQ5160313-A.R1</u> , dated: <u>2</u>	5-Mar-2022	Rail Impact Test Certific	cate/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>	
TC Impact Approved: <u>Yes</u>					
PRESSURE TEST					
Test Pressure of Tank: 6.0 bar, dated: 04-Jun-2023		Test Pressure of Heating System: 6.0 bar, dated: 02-Jun-2023			
_eak Proof Test of Containe	er: <u>1.0</u> bar, dated: <u>06-Jun-2</u>	023			
Approved Commodities: Cc	mpatibilities commodities a	s per T11 / L4BN			
Portable Tank Instruction: T11		ADR/RID Tank Code: <u>L4BN</u>			
04/0	6/2023 P Æ)	CSC Plate Stamping Da	ate: <u>06/2028</u> or ACEP №.: <u>N/A</u>	
			Next Inspection Date: 1	2/2025	
Stamping ta	-		· -		
	ments: <u>The compatibilities I</u> cial provisions markings are			e relief devices/vessel/gaskets are the responsibility of th	
Issued on: <u>09-Jun-2023</u> at .			ABS	Field Office: Shanghai, Chi	
Request Reviewed and N	IO Conflict of Interest Identifi	ed			
DTE: This Certificate evidenci committees, its clients of guides, standards, or oth of Shipping who shall re	es compliance with one or more or other authorized entities. This ner criteria of American Bureau or main the sole judge thereof. Nof utrer. seller. supplier. repairer. c	of the Rules, guides, stander Certificate is a representation of Shipping. The validity, appli- hing contained in this Certific pretator, or other entity of any	Tay of the ofference American n only that the October of store cability and interpret was written ate or in any Reputy student per (warranty express of publication)	Bueau of Shipping and is issued solely for the use of the Bureau ed herein has been found to comply with one or more of the Ru ertificate is governed by the Rules and standards of American Bur remplation of this Certificate shall be deemed to relieve any desig	