

## American Bureau of Shipping UN Portable Tank/Tank Container Initial Certificate

Owner & address	<u>Falcon Lease Pte</u> <u>60 PAYA LEBAR</u>	<u>Ltd</u> ROAD, #12-05, PAYA LEBA	<u>R SQUAR</u> E,SINGAPORE.	409051 Owner No.: FLNU 600901-0
Manufacturer & address	Jing Jiang Asian-	Pacific Logistics Equipment C Avenue, JingJiang City, Jiang	o., Ltd	Serial No.: <u>2210644</u>
/anufacturer's Model Nº.: <u>/</u>		wende, ungolang eity, uang		
APPLICABLE RULES, RE		JARDS	US DOT Identification Co	
BS Approval Ref. № <u>T2382295</u>			US DOT Approval: 49 CFR <u>§178.273, §178.274, §178.275</u>	
CSC Approval Reference: USA/AB-124/22			IMDG Approval Reference	
Customs Approval Reference: USA/124-AB/22				val Number: NL/AB-124/22
International Union of Railways (UIC): IRS 50592			Sec. 6.8 ADR/RID Approval Number: NL/AB-124/22	
Other(s): TC, ISO 668, 1161, 6346, 1496-3			US DoT SP: N/A and/or TC Equiv. Cert.: N/A	
ONTAINER CHARACTER	RISTICS			
SO Size/Type Code: <u>22K2</u>				
Overall Length: <u>6058</u> mm		Widtl	h: <u>2438</u> mm	Height 2591 mm
Maximum Operating Gross	Mass: <u>36000</u> kg	Tar	e: <u>3760</u> kg	Max. Permissible Payload: 32240 kg
Ilowable Stacking Load for	r 1.8 g: <u>216000</u> kg		Transverse Racking Test	t Force: <u>150000</u> newtons
ANK CHARACTERISTIC	6			
esign Code: <u>ASME BPVC</u>	VIII Div. 1 & EN 14025		Liquid Capacity at 20°C:	25970 liters (total)
Overall Tank Length: 6029	mm		Outside Tank Diameter:	<u>2423</u> mm
lead Matl Spec.: <u>SANS 50</u>	028-7:1.4402	Head Thickness: <u>4.6</u> mm	(as built after forming)	Head Corrosion Allowance: 0.2 mm
Shell Matl Spec.: <u>SANS 500</u>	028-7:1.4402	Shell Thickness: 4.6 mm	(as built)	Shell Corrosion Allowance: 0.42 mm
Equiv. Reference Steel Thio	ckness: <u>6</u> mm			
MAWP: <u>4.0</u> bar			MAWP of Heating Syster	n: <u>4.0</u> bar
External Design Pressure: (	Design Pressure: <u>0.41</u> bar		Design Temperature Range: Min.: <u>-40</u> °C; Max.: <u>130</u> °C	
pating/Lining: Type: <u>N/A</u> & Thickness: <u>N/A</u> mm			Insulation: Type: Rockwool & Thickness: 50 mm	
Baffles: <u>N/A</u> Quantity: <u>N/A</u>			Cladding: Type: <u>GRP</u> & Thickness: <u>1.8 / 2.0</u> mm	
Discharge: <u>Bottom</u>			Bottom Discharge No. of	Closures in Series: <u>3</u>
PRESSURE RELIEF DEVI	CES			
	1 <sup>st</sup> ; Quantity: <u>1</u>		2 <sup>nd</sup> ; Quantity: <u>N/A</u>	3 <sup>rd</sup> ; Quantity: <u>N/A</u>
Manufacturer	GUARD			
Catalog Number	<u>AMF48001-00</u>		=	
Set Pressure	<u>4.4</u> bar		bar	<u></u> bar
Rupture	<u>N/A</u> bar		bar	<u></u> bar
Capacity (each)	<u>4.67</u> m <sup>3</sup> /s		<u></u> m³/s	<u></u> m³/s
Fotal Capacity: <u>4.67</u> m <sup>3</sup> /s				
		H. A. <sup>1</sup> . I <sup>1</sup>		
<u>3" Bottom Discharge, 3" To</u>	p Discharge Provision, 1.5	Air line		
TESTING INFORMATION				
Prototype Test Certificate: <u>S</u> TC Impact Approved: Yes	<u>SQ5160313-A.R1</u> , dated: <u>2</u>	<u>:5-Mar-2022</u>	Rail Impact Test Certifica	ate/Report: <u>SQ5038404-A</u> , dated: <u>21-Jan-2022</u>
PRESSURE TEST				
Fest Pressure of Tank: 6.0	bar, dated: 03-Jun-2023		Test Pressure of Heating	System: <u>6.0</u> bar, dated: <u>02-Jun-2023</u>
_eak Proof Test of Containe	· · · · · · · · · · · · · · · · · · ·	2023		
Approved Commodities: Co	mpatibilities commodities a	as per T11 / L4BN		
Portable Tank Instruction: T			ADR/RID Tank Code: L4	BN
02/0	6/2023 P Æ	3	CSC Plate Stamping Dat	e: <u>06/2028</u> or ACEP Nº.: <u>N/A</u>
		<i>,</i>	Next Inspection Date: 12	/2025
Stamping ta	-	1	·	
		between commodities and se e the responsibility of the own		relief devices/vessel/gaskets are the responsibility of th
Issued on: <u>09-Jun-2023</u> at .			ABS	Field Office: Shanghai, Chi
Request Reviewed and N	O Conflict of Interest Identif	ied.		
DTE: This Certificate evidence	es compliance with one or mor	e of the Rules, guides, standard,	or other criterion American B	ueau of Shipping and is issued solely for the use of the Bureau ed herein has been found to comply with one or more of the Ru ritificate is governed by the Rules and standards of American Bur